


47 UNIFLEX sockets

SAE AS 954-E (American sizes),
HPQ high performance steel, chrome plated.




Code		d ₁ mm	d ₂ mm	d ₃ mm	L mm	t ₁ mm	t ₂ mm	$\Delta\Delta$ g	
02040010	10	14.3	17.5	9	45.5	7	12	51	1
02040011	11	15.6	17.5	10	47.5	11	14	55	1
02040012	12	16.9	17.5	11	48	11	14.5	54	1
02040013	13	18.3	17.5	12	48	12	14.5	53	1
02040014	14	19.4	17.5	13	48.5	13	14.5	55	1
02040015	15	20.6	17.5	14	48.5	13	14.5	56	1
02040016	16	21.8	17.5	15	51.5	14	17	58	1
02040017	17	23	17.5	16	53.5	15	18.5	63	1
02040018	18	24.2	17.5	17	54.5	16	18.5	61	1
02040019	19	25.5	17.5	18	57	16	21	68	1

47a UNIFLEX sockets

Code		d ₁ mm	d ₂ mm	d ₃ mm	L mm	t ₁ mm	t ₂ mm	$\Delta\Delta$ g	
02440020	5/16	11.7	17.5	7	45.5	7	12.5	50	1
02440024	3/8	13.7	17.5	8.5	45.5	7	12	50	1
02440028	7/16	15.8	17.5	10	47.5	11	14	54	1
02440032	1/2	18.3	17.5	11.5	47.5	11.5	14	57	1
02440034	9/16	19.7	17.5	13.1	48.5	13	14.5	55	1
02440036	5/8	21.6	17.5	15	51.5	14	17	59	1
02440038	11/16	23.5	17.5	16.3	53.5	16	18.5	58	1
02440040	3/4	25.5	17.5	18	57	16	21	67	1

45aSP Sockets spline-drive


MS-33787, MIL-W-8982,
HPQ high performance steel, chrome plated.



Code	Spline size		d ₁ mm	d ₂ mm	d ₃ mm	L mm	t ₁ mm	t ₂ mm	$\Delta\Delta$ g	
02011012	12	3/8	13.7	16.5	8.6	26.5	9	15	24	1
02011014	14	7/16	16	17.3	10.4	28	11	14.5	37	1
02011016	16	1/2	18	18.3	12.2	28	11.5	14	28	1

45aPSP Socket spline-drive


MS-33787, MIL-W-8982, for disassembling jet engines, series CFM 56,
HPQ high performance steel, gun finish.



Code	Spline size		d ₁ mm	d ₂ mm	d ₃ mm	L mm	t ₁ mm	t ₂ mm	$\Delta\Delta$ g	
22410028	14	7/16	18.8	18.8	10.4	28	11	14.5	36	10

46aSP Sockets spline-drive


extra deep bolt clearance,
MS-33787, MIL-W-8982,
HPQ high performance steel, chrome plated.



Code	Spline size		d ₁ mm	d ₂ mm	d ₃ mm	L mm	t ₁ mm	t ₂ mm	$\Delta\Delta$ g	
02021012	12	3/8	13.7	16.5	8.6	54	9	42.5	52	1
02021014	14	7/16	16	17.3	10.4	54	11	42.5	63	1

45aP Socket


ASME B 107.1, Fed. Spec. GGG-W-641,
SAE AS 954-E (test loads),
for disassembling jet engines, series CFM 56,
HPQ high performance steel, gun finish.



Code		d ₁ mm	d ₂ mm	d ₃ mm	L mm	t ₁ mm	t ₂ mm	$\Delta\Delta$ g	
02430020	5/16	11.9	16.5	8.1	25	7	13.5	19	10

46aP Socket

Plastic coating protects sensitive alloy wheels,
HPQ high performance steel, chrome plated.



Code		d ₁ mm	d ₂ mm	d ₃ mm	L mm	t ₁ mm	t ₂ mm	$\Delta\Delta$ g	
22420024	3/8	16.5	16.5	8.4	54	20	42.5	44	1