

3M Industrial Adhesives & Tapes Division
3M™ Specialty High Temperature Masking Tape 501E

101E 201E 301E 401E 501E

The highest
degree
of industrial
performance

501E



3M

3M™ Specialty High Temperature Masking Tape 501E

3M™ Specialty High Temperature Masking Tape 501E stands up to the heat *and* your high standards. Built on a foundation of innovation, 501E is specifically designed for industrial paint applications where surface temperatures can reach up to 160°C. With the perfect blend of strength, flexibility and adhesion, 501E delivers the consistently superior results you've come to expect from 3M.

Product Highlights

- Specialty high temperature tape for indoor use
- Highest performing paper masking tape
- Exceptionally conformable to irregular surfaces
- Creates super sharp paint lines
- Smooth backing reduces finger abrasion
- Removes cleanly in one piece with no residue
- Ideal for all high temperature paint baking, fascia painting and pipe coating applications
- Withstands surface temperatures up to 160°C for one hour



Superior adhesion



Withstands surface temperatures up to 160°C



Removes cleanly



Consistently superior finishes

3M™ Specialty High Temperature Masking Tape 501E

Tape Size	Rolls/Case	SKU
1526 mm x 50 m	9	UU001569373
18 mm x 50 m	48	UU001568557
24 mm x 50 m	36	UU001568565
36 mm x 50 m	24	UU001568573
48 mm x 50 m	20	UU001568581
72 mm x 50 m	12	UU001571536



Learn more about 3M™ Industrial Masking Tapes at 3M.com/maskingmadesimple

PRODUCT USE: All statements, technical information and recommendations contained in this document are based upon tests or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and performance of a 3M product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method of application. **WARRANTY AND LIMITED REMEDY:** Unless stated otherwise in 3M's product literature, packaging inserts or product packaging for individual products, 3M warrants that each 3M product meets the applicable specifications at the time 3M ships the product. Individual products may have additional or different warranties as stated on product literature, package inserts or product packages. 3M MAKES NO OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's application. If the 3M product is defective within the warranty period, your exclusive remedy and 3M's and seller's sole obligation will be, at 3M's option, to replace the product or refund the purchase price. **LIMITATION OF LIABILITY:** Except where prohibited by law, 3M and seller will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.



3M Industrial Adhesives & Tapes Division

3M is a trademark of 3M Company.
Please recycle.
© 3M 2015. All rights reserved.