

Product datasheet

uvex 1 business 8428 1-3

Safety shoe DIN EN ISO 20345:2022 S3L FO SR

Sizes: 39 - 52 | Width: 10, 11, 12











AREA OF APPLICATION

The light application covers all areas in which work is carried out indoors in particular and which do not place high demands on the physical properties of the outsole of a safety shoe.

OUTSOLE

Polyurethane outsole



- PU outsole
- antistatic
- short-term heat-resistant up to 120°C
- excellent slip resistance (SR)
- oil- and fuel resistant (FO)
- free of silicones, plasticisers and other substances that interfere with wetting agents





FEATURES	
Upper material	breathable microvelour (clima zone)
	water-repellent (WPA)
	suitable for people allergic to chrome
Lining material	breathable textile
Fastening	• laces
Comfort	soft padding on collar
Insock	removable comfortable insock
PROTECTIVE FEATUR	RES
Toe cap	steel protective toe cap
Penetration resistance	metal-free, textile penetration resistance
CERTIFICATES	
uvex medicare	 certified for orthopaedic insocks according to the description in DGUV 112-191
100% vegan	certified free from animal ingredients and products
10070 (09011	additional protection for people with allergies and
	intolerances
ESD	protection against electrostatic charge according to EN
	61340-4-3 und EN 61340-5-1
SUSTAINABILITY	
Recycled/sustainable materials	removable insock and heel cap made wholly or partly
	from recycled materials
	free from harmful substances in accordance with the
ACCECODICE/CBADE	uvex restricted substances list
ACCESORIES/ SPARE	
Replacement insock	• 9515 7-9
Laces	• black 9599700