

11-939

Lightest weight gloves with cut + oil protection for enhanced safety









Ultralight, fully coated cut-resistant and oilrepellent work gloves

- Specialized protection: ANSI A2/ISO B cut protection guaranteed, while RIPEL[™] Liquid Repellence Technology prevents oil and liquid contact with the skin
- Targeted defenses: The HyFlex[®] 11-939's reinforced thumb crotch delivers 12x more resilience in the thumb area
- Improved durability: FORTIX[™] Abrasion Resistance foam coating makes these HyFlex[®] gloves 12x more abrasion-resistant
- Lightened feel: HyFlex[®] 11-939 PPE gloves' ultralight 18-gauge design and ERGOFORM[™] Technology deliver superb dexterity
- Enhanced grip: ANSELL GRIP[™] coating treatment reduces the force needed to maintain grip, preventing workplace injuries
- Elevated comfort: ZONZ[™] Comfort Fit's knitting and stitch design reduces hand fatigue, ensuring greater comfort

Industries

- Automotive
- Automotive Aftermarket
- Machinery and Equipment
- Metal fabrication
- Agriculture
- Emergency Medical Services
- Oil and gas
- Utilities
- Warehousing



Applications

- Inspection, selecting, checking parts
- · Assembly & inspection of components
- Picking, fastening components
- Chassis assembly, body trimming
- Adjusting parts, systems
- Delivery of parts to production line
- Equipment repair & maintenance
- Engine transmission and repair
- Oil, fluids and filter change
- Inspection (picking, checking and marking)
- Feeding the press and removing spare parts from it
- Fastening components, parts
- Adjusting panels parts components
- Press shop operations





11-939

Lightest weight gloves with cut + oil protection for enhanced safety

Key Features

- RIPEL[™] Liquid Repellence: Defense from oil and chemicals
- Reinforced thumb crotch: 12x greater durability around the thumb*
- Ultralight 18-gauge design: All-day comfort and dexterity *compared to competitor gloves lacking this feature

Technologies

















Performance Standards & Regulatory Compliance

REACH Compliant















Specifications

| BRAND STYLE | DESCRIPTION | Gauge | SIZE | LENGTH | COLOR | PACKAGE |
|----------------------------|--|-------|-----------------------|-------------------------------|-------------------|---|
| HyFlex [®] 11-939 | Finishing: Fully Coated Coating Material: Foam Nitrile Liner Material: Dyneema [®] Diamond Technology Cuff Style: Knitwrist | 18 | 6, 7, 8, 9, 10, 11 | 212-261 mm / 8.3- 10.3 in. | Black and Grey | 12 pairs / polybag, 12 polybags per case = 144 pairs / case |

For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region

Ansell Healthcare Europe NV Ansell Healthcare Europ Riverside Business Park Blvd International, 55 1070 Brussels, Belgium T: +32 (0) 2 528 74 00 F: +32 (0) 2 528 74 01

Latin America & Caribbean Region

Ansell Commercial Mexico S.A. de C.V. Blvd. Bernardo Quintana No. 7001-C, BIVO. Bernardo Quintana No. 70' Q7001 Torre II. Suites 1304, 1305 y 1306. Col. Centro Sur, c.p. 76079 Queretaro, Qro. Mexico T: +52 442 248 1544 / 248 3133

North America Region

Ansell Healthcare Products LLC 111 Wood Avenue South, Suite 210 Iselin, NJ 08830, USA T: +1 800 800 0444 F: +1 800 800 0445

Canada

Ansell Canada 105 Lauder Cowansville, QC J2K 2K8 T: +1 800 363 8340

Australia

Ansell Limited Ansell Limited Level 3,678 Victoria Street, Richmond, Vic, 3121 Australia T: +61 1800 337 041 F: +61 1800 803 578

Asia Pacific Region

Ansell Global Trading Center Ansell Global Trading Center (Malaysia) Sdn Bhd Prima 6, Prima Avenue Block 3512, Jalan Teknokrat 6 T: +603 8310 6688 F: +603 8310 6699

Ansell, [®] and [™] are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking © 2021 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

