

435QR/3 QuickRelease set



Content:
Ratchet 435QR
Extension 427/3QR, 76 mm
Extension 427/6QR, 160 mm
Extension 427/10QR, 240 mm



Code	L mm	b mm	a mm	△△ g	☐
96 12 11 03	722		17	275	1

435SG-QR QuickRelease ratchet



reversible, 30 teeth,
with QuickRelease safety locks and steel handle,
DIN 3122/ISO 3315.



Code	L mm	b mm	a mm	△△ g	☐
12 11 00 30	193	29	17	275	1

435B Bit ratchet

reversible,
with inside hexagon 5/16",
DIN 3126/ISO 1173 D 8 for
Bits Screwdriver sockets 5/16",
30 teeth.
Internal hex drive with a collar-thrust spring (registered design).
Bits are easy to insert, lock securely in position and can be removed just
as easily; even hex bits with a wide groove (Type E, DIN 3126/ISO 1173).



Code	L mm	b mm	a mm	△△ g	☐
12 13 00 11	193	29	17	220	1

445 Ratchet adaptor

reversible, 20 teeth.



Code	L mm	∅ mm	△△ g	☐
12 14 00 00	53	30	135	1

452 Flexible joint ratchet

reversible, 60 teeth, handle may be
raised or lowered by approx. 90°.
Lockable in following positions:
straight, 30° up, 60° up, 30° down.
Unlocked by depressing button in handle, registered design.



Code	L mm	b mm	a mm	△△ g	☐
12 26 00 01	300	34	24	500	1

453 Speeder brace

with steel handle,
for greater axial power
transmission, detachable palm
head, working radius 85 mm,
DIN 3122/ISO 3315.



Code	L mm	△△ g	☐
12 10 00 02	408	619	1

424 Flexible handle

DIN 3122/ISO 3315.



Code	L mm	△△ g	☐
12 06 00 10	253.5	222	5

425 Sliding T-handle

DIN 3122/ISO 3315.



Code	L mm	△△ g	☐
12 07 00 00	165	133	5

425QR QuickRelease sliding T-handle




with QuickRelease safety locks.



Code	L mm	△△ g	☐
12 07 10 00	165	148	1


444 T-handle extension



Code	L ₁ mm	L ₂ mm	△△ g	☐
12 02 00 01	455	190	437	5

427 Extensions

DIN 3123/ISO 3316.



Code	size	L mm	d mm	△△ g	☐
12 01 00 05	1.5	38	17	36	5
12 01 00 01	3	76	17	67	5
12 01 00 06	5	125	17	104	5
12 01 00 02	6	160	17	127	5
12 01 00 03	10	240	17	188	5
12 01 00 04	18	455	17	345	5