

- AUTOMATIC LUBRICATOR (3 MONTH)

Item #	EAN	Product
735600	3660338017315	Automatic Lubricator (3 month)

- Description

- Spartex automatic lubricators are designed to lubricate industrial machinery with the right quality of lubricant and at the right time to improve machine reliability & reduce unscheduled shutdowns or production losses whilst enabling workers' safety. Prevents damage & reduces wear.

- Application

- Food & beverage industry
- Transport, shipping & traffic engineering
- Fresh & waste water engineering
- Mining & power industry
- Elévation & elevator industry
- Machine & tool industry

- Characteristics

Cap colour	Blue
Operating time	3 month
Lubricant capacity (cm ³)	120
Discharge capacity at 25°C (g/day)	1,2
Discharge capacity at 35°C (g/day)	1,5
Lubricant	Multi-purpose EP, NLGI 2
Lubricant thickener	Li, Ca
Operating temperature (°C)	-30 to +120
Drop point of lubricant (°C)	155
Lubricant specification	Universal DIN KP2K-30
Delivery of lubricant	Automatic without external power supply
Connecting thread	G 1/4" male

- Instructions

- Screw in the starter cap by hand & tighten down firmly (you wil hear the seal break whilst completing this action). Record chage over date. Pre-grease bearing before first installation. Install unit hand tight into grease point

- Packaging

Dimensons LxWxH (mm)	360 x 300 x 105
Weight (Kg)	6,7
Packing unit	20,0

