# **DATASHEET**



## 100A 3 Phase Single Tariff MID Approved Product Specification **Electricity Meter Direct Connected**


### Product Ref: AEL3

#### **Technical Features:**

- · Date, time and tariff data programmable by authorised personnel - Invoicing data stored for 12 months
- Consumed total power, lid openings and demand data collected
- Auto trouble-shooting feature
- Optic port for data transmission
- Consumed active energy indicated via LEDs
- Automatic summer/winter day light saving time switchover
- Data requests still accessible during power failure



Voltage Rating	4 Wire (TP&N) 230 / 400V
Current Rating	Max = 100A
IP Rating	IP54
Weight	689g
Operating Temperature	-40 - +70°C
Frequency	50Hz
Insulation	4kV RMS 50Hz
Impluse Withstand	12kV 1.2/50μs 500ohm source
IrDA Baud Rates	2400, 4800 or 9600
Serial Baud Rates	2400 or 4800
Pulse Voltage	6kV
Meter Constant	1000 imp/kWh
Mounting	Wall
Colour	Light Grey
Material	PVC
Class	Class B (MID)
Compliance	CE, UKCA
Guarantee	1 Year
Standards	EN 50470-1, EN 50470-3
Depth	60mm
Height	285mm
Width	175mm



Errors and omissions excepted (E&OE). All information is subject to change without notice and is correct at the time of print. Refer to issue number and date below.