



Description

PROTEAN PTFE Dry Film Lubricant is a NSF H1: registered PTFE-enhanced lubricant engineered for use in Food & Beverage processing environments where conventional oils and greases are undesirable due to their dirt attracting nature. Ideal for lubricating links, pins and slides.

Also suitable for use in Packaging, Pharmaceutical and other cleanroom environments.

Outstanding Features

- NSF: H1 registered
- PTFE-based lubricant for excellent anti-stick properties
- Effective release agent
- Non-toxic film
- Temperature range: -20°C to +270°C
- 360° valve for inverted use

Directions for Use

- Store out of direct sunlight and below +50°C (ideally between 10°C and 25°C)
- Consult the safety data sheet prior to use
- Shake aerosol well before use
- For best results, use only on clean and dry areas that are free from dirt

Technical Data

Category	H1 (lubricant with incidental food contact, for use in and around food processing areas)
NSF Certificate No.	139294 Does not contain any genetically modified ingredients, nut oils or animal derivatives
Appearance	White
Odour	Slightly sweet
Propellant(s)	Propane / butane
Flammability	Extremely flammable aerosol
Storage	Below +50°C
Flash Point	-60°C
Temperature range	-20 to +270°C
Relative Density	0.72
Solubility	Insoluble in water
Pack Sizes	12 x 400ml cans



The content of this data sheet is given in good faith but without warranty.