

Project..... Comments.....

Fixture Type..... Prepared By.....

### Product Description:

Suitable for control of dimmable compact fluorescent and LED lamps, dimmable electronic transformers, LED drivers, toroidal transformers and tungsten lamps. Integrated trimming potentiometer allows CFL and LED lamps to be set at a minimum level to prevent them going out or flickering at the bottom of the dimmer range. Leading edge phase control. For use with resistive and inductive loads. Integrated over-temperature protection fuse. Module case ultrasonically sealed to reduce dimmer buzzing. Smooth dimming operation from 0-100% light output. May be fitted to most dimmer plates. One or two way switching. Complies with the latest Electrical Safety standard for dimmer switches EN 60669-2-1:2000. EMC compliance - EN 55015. 1 Year guarantee.

### Product Image & Dimensions:



Length	62 mm
Width	26 mm
Height	25 mm

### Product Specifications:

- Input Voltage (Min): 220 V
- Input Voltage (Max): 250 V
- Input Voltage Type: AC
- Nominal Power: 60-400W
- Length: 62 mm
- Width: 26 mm
- Height: 25 mm
- Guarantee: 1 Year

### Compliance & Approvals:



### SKU Table and Ordering:

SKU Code	EAN	Qty
AU-DSP400X	5055155459345	<input type="text"/>

### Warranty:

For available warranty information for this product, please visit:

<http://gb.auroralighting.com/Products/Control/Rotary-Dimmers/60-400VA-1-Gang-2-Way-Zero-Cross-Rotary-Dimmer.aspx>

#### UK Sales

16 Alban Park  
Hatfield Road, St. Albans  
United Kingdom  
PH: +44 (0) 1727 83 66 11  
FX: +44 (0) 1727 83 66 22

#### UK Distribution

Apex Park, 6 Little Burrows  
Burrowfields, Welwyn Garden City  
AL7 4SW  
United Kingdom  
PH: +44 (0) 1707 35 18 20  
FX: +44 (0) 1727 35 18 21