

## SAFETY GLASSES G-RACK

Item #	EAN	Product
865637	3660338198939	Clear lens
865639	3660338198946	Smoke lens

### Description

Standard : EN166  
 Light, supple safety glasses, comfortable in the modern design.  
 Branches with supple tips in TPE. Supple nose.  
 sturdy, protective, stylish, comfortable and lightweight.  
 Weight : 24 g.

### Characteristics

- Delivered with a microfibre pouch.
- Lenses: PC – 2,2 mm – Curve 9,5
- Frame: PC / Temples : Nylon + TPE



### Instructions & storage

**CLEANING:** The lenses should be cleaned regularly.

**MAINTENANCE:** Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case. **STORAGE:** All products must be stored in a dry and clean environment

### Standards and certifications

**UK  
CA**

Lens marking : 2C-1.2 1 FT KN

Lens marking (smoke): 5-2.5 1 FT KN

Frame marking : CE EN166 FT

K - Resistance to surface damage by fine particles

The anti-scratch coating K provides enhanced scratch-certified coating.

N - Resistance to fogging

The anti-fog coating N is an anti-fog treatment certified.

#### LENS MARKING

##### Optical class symbols:

1. Continuous work

##### Mechanical strength symbols:

**F.** Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s  
 Maximum protection for glasses.

**T.** The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

##### Others symbols:

**K.** Resistance to surface damage by fine particles (optional)

**N.** Resistance to fogging (optional)

#### FRAME MARKING

**EN 166:** guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

**F.** Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s  
 Maximum protection for spectacles.

**T.** The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

**K.** Resistance to surface damage by fine particles (optional) **N.** Resistance to fogging (optional)

### Packaging

- Individual plastic Bag / 10 safety spectacles per inner box / Carton of 200 units