



Industrial Contractor Tower (3T Design)



Product Dimensions (Single Width)

PRODUCT SKU (3T)	APPROX. WORKING HEIGHT (M)	PLATFORM HEIGHT (M)	OVERALL HEIGHT (M)	FRAME WIDTH (M)	FRAME DEPTH (M)	STABILISER WIDTH (M)	STABILISER DEPTH (M)	WEIGHT 3T (KG)
3012-000	3.0	1.4	2.7	2.0	0.7	-	-	77.0
3012-001	3.5	1.9	3.1	2.0	0.7	4.7	3.5	100.0
3012-002	3.9	2.3	3.6	2.0	0.7	4.7	3.5	105.0
3012-003	4.4	2.8	4.1	2.0	0.7	4.7	3.5	130.0
3012-004	4.9	3.3	4.5	2.0	0.7	4.7	3.5	136.0
3012-005	5.3	3.7	5.0	2.0	0.7	4.7	3.5	139.0
3012-006	5.8	4.2	5.5	2.0	0.7	4.7	3.5	147.0
3012-007	6.3	4.7	5.9	2.0	0.7	4.7	3.5	150.0
3012-008	6.7	5.1	6.4	2.0	0.7	5.8	4.6	156.0
3012-009	7.2	5.6	6.8	2.0	0.7	5.8	4.6	167.0
3012-010	7.7	6.1	7.3	2.0	0.7	5.8	4.6	173.0
3012-011	8.1	6.5	7.8	2.0	0.7	5.8	4.6	200.0
3012-012	8.6	7.0	8.2	2.0	0.7	5.8	4.6	206.0
3012-013	9.1	7.5	8.7	2.0	0.7	5.8	4.6	209.0
3012-014	9.5	7.5	9.2	2.0	0.7	5.8	4.6	215.0

Product Dimensions (Double Width)

PRODUCT SKU (3T)	APPROX. WORKING HEIGHT* (M)	PLATFORM HEIGHT (M)	OVERALL HEIGHT (M)	FRAME WIDTH (M)	FRAME DEPTH (M)	STABILISER WIDTH (M)	STABILISER DEPTH (M)	WEIGHT (KG)
3015-000	3.0	1.4	2.7	2.0	1.4	-	-	96.0
3015-001	3.5	1.9	3.1	2.0	1.4	-	-	104.0
3015-002	3.9	2.3	3.6	2.0	1.4	-	-	111.0
3015-003	4.4	2.8	4.1	2.0	1.4	4.7	4.1	130.0
3015-004	4.9	3.3	4.5	2.0	1.4	4.7	4.1	161.0
3015-005	5.3	3.7	5.0	2.0	1.4	4.7	4.1	166.0
3015-006	5.8	4.2	5.5	2.0	1.4	4.7	4.1	176.0
3015-007	6.3	4.7	5.9	2.0	1.4	4.7	4.1	180.0
3015-008	6.7	5.1	6.4	2.0	1.4	4.7	4.1	188.0
3015-009	7.2	5.6	6.8	2.0	1.4	5.8	5.2	201.0
3015-010	7.7	6.1	7.3	2.0	1.4	5.8	5.2	210.0
3015-011	8.1	6.5	7.8	2.0	1.4	5.8	5.2	237.0
3015-012	8.6	7.0	8.2	2.0	1.4	5.8	5.2	248.0
3015-013	9.1	7.5	8.7	2.0	1.4	5.8	5.2	251.0
3015-014	9.5	7.9	9.2	2.0	1.4	5.8	5.2	260.0
3015-015	10.0	8.4	9.4	2.0	1.4	5.8	5.2	264.0
3015-016	10.4	8.8	9.8	2.0	1.4	5.8	5.2	273.0
3015-017	10.9	9.3	10.0	2.0	1.4	5.8	5.2	278.0
3015-018	11.4	9.8	10.8	2.0	1.4	5.8	5.2	287.0
3015-019	11.8	10.2	11.2	2.0	1.4	5.8	5.2	291.0
3015-020	12.3	10.7	11.7	2.0	1.4	5.8	5.2	300.0
3015-021	12.8	11.2	12.2	2.0	1.4	5.8	5.2	327.0
3015-022	13.2	11.6	12.6	2.0	1.4	5.8	5.2	336.0
3015-023	13.7	12.1	13.1	2.0	1.4	5.8	5.2	341.0



Technical Description

For higher risk or more time consuming work at height, ladders or stepladders may be an unsuitable choice. For these tasks, our range of industrial grade aluminium scaffold towers are ideal. Easy to assemble and dismantle using either of the HSE endorsed and industry approved 3T (Through The Trap) or AGR (Advance Guard Rail) systems, the operative installs collective fall prevention before accessing the working platform. Ask our team about our PASMA accredited training facilities in order to fulfil your training requirements.

- » Double width scaffold tower
- » 50mm scaffold tube construction
- » Heavy-duty spigot for maximum strength
- » Crimped abuse resistant joints
- » Toe-board and guardrails for additional security
- » Fully compliant 3T/AGR options

Standards & Classification

- » Max Safe Working Load for Structure 750kg
- » Max Safe Working Load for Platform 250kg
- » EN1004

Warranty

- » 5 Years