



[Representative image of product]

Features

- Large heavy-duty ridge hook with rubber covered anti-slip locating bar
- Large wheels for easy manoeuvring on the roof
- High grip rubber coated support bearers for tile protection

Product Dimensions

SKU	Rungs /Sections	Closed Length (mm)	Last Climbing Height	Approx. Working Height ¹ (mm)	Extended Length (mm)	Width (mm)	Depth (mm)	Nett Weight (kg)
1305-000	17 x 1	4350		1600	4350	380		9.8
1305-001	19 x 1	4950		1600	4950	380		10.7
1305-002	21 x 1	5550		1600	5550	380		11.8
1305-011	11+9 x 2	3000		1600	4830	400		12.0
1305-012	13+11 x 2	3600		1600	6050	400		13.8
1305-013	15+13 x 2	4000		1600	6730	400		14.7
1305-014	17+15 x 2	4600		1600	7930	400		16.5

¹ Working height is calculated as 1,600mm plus platform height or last climbing tread, whichever is appropriate. Ladders set at an angle of 75° degrees.

Specifications

- Warranty: 3-year
- Max Load: 175kg
- Standard:
- Material: Aluminium
- Commodity Code: 76169990
- Country of Origin: GB
- Recommended Usage: Regular

Common Dimensions

- Rung Depth: 25mm
- Distance Between Rungs: 275mm

Availability & Delivery

Stock item. Delivery next day.

(See exceptions, if applicable, overleaf)

Product Description

Rugged box-section stiles offer the combination of lightweight usability and strength needed for roof work. The ladder is fitted with a roof hook to secure on the central ridge with wheels to run the ladder up the roof. Protected bearers fitted at intervals help spread the load across the roof tiles.

Shipping Dimensions

SKU	Barcode	Shipping Length (mm)	Shipping Width (mm)	Shipping Depth (mm)	Shipping Volume (m ³)	Gross Weight (kg)
1305-000	5060169481947	4500	410	625	1.153	11.0
1305-001	5060169481954	5000	410	625	1.281	12.0
1305-002	5060169481961	5500	410	625	1.409	13.0
1305-011	5060169482029	3000	410	625	0.769	16.0
1305-012	5060169482036	3500	410	625	0.897	18.0
1305-013	5060169482043	4000	410	625	1.025	20.0
1305-014	5060169482050	4500	410	625	1.153	22.0