


Turning Insert – Positive rhombic 80°

CCMT / CCGT / CCMW

Tiger-tec® Gold



Indexable inserts

	Designation	l mm	r mm	f mm	ap mm	P						M				K			N		S					
						HC						HC				HC			HC		HC		HC			
						WKP01G	WPP10G	WPP20G	WMP20S	WPP30G	WEP01C	WEP10C	WSM01	WSM10S	WMP20S	WSM20S	WSM30S	WKP01G	WKK10S	WKK20S	WNN10	WN10	WSM01	WSM10S	WSM20S	WSM30S
	CCMT060202-FM4	6,45	0,2	0,04–0,12	0,1–1,0				☹					☹	☹	☹	☹						☹	☹	☹	☹
	CCMT060204-FM4	6,45	0,4	0,05–0,16	0,1–1,5				☹					☹	☹	☹	☹						☹	☹	☹	☹
	CCMT060208-FM4	6,45	0,8	0,08–0,20	0,1–1,5				☹						☹	☹	☹							☹	☹	☹
	CCMT09T302-FM4	9,67	0,2	0,04–0,12	0,1–1,0				☹					☹	☹	☹	☹						☹	☹	☹	☹
	CCMT09T304-FM4	9,67	0,4	0,05–0,16	0,1–1,5				☹					☹	☹	☹	☹						☹	☹	☹	☹
	CCMT09T308-FM4	9,67	0,8	0,08–0,20	0,1–1,5				☹					☹	☹	☹	☹						☹	☹	☹	☹
	CCMT120404-FM4	12,9	0,4	0,05–0,16	0,1–1,5									☹		☹	☹						☹	☹	☹	☹
CCMT120408-FM4	12,9	0,8	0,08–0,20	0,1–1,5									☹		☹	☹						☹	☹	☹	☹	
	CCMT060202-FP4	6,45	0,2	0,04–0,12	0,1–1,0	☹	☹	☹					☹					☹								
	CCMT060204-FP4	6,45	0,4	0,05–0,16	0,1–1,5	☹	☹	☹	☹				☹					☹								
	CCMT060208-FP4	6,45	0,8	0,08–0,20	0,1–1,5	☹	☹	☹	☹									☹								
	CCMT09T302-FP4	9,67	0,2	0,04–0,12	0,1–1,0	☹	☹	☹	☹									☹								
	CCMT09T304-FP4	9,67	0,4	0,05–0,16	0,1–1,5	☹	☹	☹	☹									☹								
	CCMT09T308-FP4	9,67	0,8	0,08–0,20	0,1–1,5	☹	☹	☹	☹				☹					☹								
	CCMT120404-FP4	12,9	0,4	0,05–0,16	0,1–1,5	☹	☹	☹	☹									☹								
CCMT120408-FP4	12,9	0,8	0,08–0,20	0,1–1,5		☹	☹	☹																		
	CCMT060204-FM6	6,45	0,4	0,08–0,25	0,3–1,6											☹	☹							☹	☹	
	CCMT060208-FM6	6,45	0,8	0,12–0,30	0,5–1,6											☹	☹							☹	☹	
	CCMT09T304-FM6	9,67	0,4	0,08–0,25	0,3–2,0											☹	☹							☹	☹	
	CCMT09T308-FM6	9,67	0,8	0,12–0,32	0,5–2,0											☹	☹							☹	☹	
	CCMT120408-FM6	12,9	0,8	0,12–0,32	0,5–2,5											☹	☹							☹	☹	
	CCMT060204-FP6	6,45	0,4	0,06–0,18	0,3–2,0		☹	☹																		
	CCMT060208-FP6	6,45	0,8	0,10–0,20	0,5–2,0			☹																		
	CCMT09T304-FP6	9,67	0,4	0,08–0,20	0,3–2,0		☹	☹																		
	CCMT09T308-FP6	9,67	0,8	0,12–0,32	0,5–2,0		☹	☹																		
	CCMT120404-FP6	12,9	0,4	0,10–0,25	0,3–2,5			☹																		
	CCMT120408-FP6	12,9	0,8	0,12–0,32	0,5–2,5			☹																		
	CCMT060204-FK6	6,45	0,4	0,06–0,18	0,3–2,0													☹	☹							
	CCMT060208-FK6	6,45	0,8	0,10–0,20	0,5–2,0													☹	☹	☹						
	CCMT09T304-FK6	9,67	0,4	0,08–0,20	0,3–2,0													☹	☹	☹						
	CCMT09T308-FK6	9,67	0,8	0,10–0,25	0,5–2,0													☹	☹	☹						
	CCMT120404-FK6	12,9	0,4	0,10–0,25	0,3–2,5													☹	☹	☹						
	CCMT120408-FK6	12,9	0,8	0,12–0,32	0,5–2,5													☹	☹	☹						
 Wiper	CCMT09T304-MW4	9,67	0,4	0,12–0,40	0,5–4,0		☹	☹								☹			☹	☹				☹		
	CCMT09T308-MW4	9,67	0,8	0,15–0,50	0,7–4,0		☹	☹								☹			☹	☹				☹		
	CCMT09T312-MW4	9,67	1,2	0,17–0,55	0,8–4,0			☹										☹	☹	☹						
	CCMT120404-MW4	12,9	0,4	0,12–0,40	0,5–4,5			☹										☹	☹	☹						
	CCMT120408-MW4	12,9	0,8	0,17–0,55	0,7–4,5		☹	☹							☹			☹	☹	☹				☹		
	CCMT120412-MW4	12,9	1,2	0,17–0,55	0,8–4,5			☹										☹	☹	☹						

See the ISO 1832 designation key for dimensions

Ordering example for the grade WPP20G: CCMT060202-FW4 WPP20G

HC = Coated carbide

HE = Coated cermet

HW = Uncoated carbide