


# Finger lever valve VHEF-LT-M32-M-G18

Part number: 4500009

**FESTO**



## Data sheet

| Feature                                  | Value                                                              |
|------------------------------------------|--------------------------------------------------------------------|
| Valve function                           | 3/2, open/closed, monostable                                       |
| Lap                                      | Zero overlap                                                       |
| Operating pressure                       | -0.095 MPa ... 1 MPa                                               |
| Actuation type                           | Manual                                                             |
| Width                                    | 20 mm                                                              |
| Standard nominal flow rate               | 750 l/min                                                          |
| Pneumatic working port                   | G1/8                                                               |
| Operating pressure                       | -0.95 bar ... 10 bar                                               |
| Design                                   | Plate seat                                                         |
| Reset method                             | Mechanical spring                                                  |
| Nominal width                            | 5.6 mm                                                             |
| Type code                                | VHEF                                                               |
| Exhaust air function                     | With flow control option                                           |
| Application note                         | Operate by hand only                                               |
| Sealing principle                        | Soft                                                               |
| Mounting position                        | Any                                                                |
| Type of control                          | Direct                                                             |
| Flow direction                           | Reversible                                                         |
| Symbol                                   | 00995684                                                           |
| Max. switching frequency                 | 0.5 Hz                                                             |
| Explosion prevention and protection      | Zone 1 (ATEX)<br>Zone 2 (ATEX)<br>Zone 21 (ATEX)<br>Zone 22 (ATEX) |
| Operating medium                         | Compressed air as per ISO 8573-1:2010 [7:-:-]                      |
| Information on operating and pilot media | Operation with oil lubrication possible (required for further use) |
| Corrosion resistance class (CRC)         | 1 - Low corrosion stress                                           |
| Temperature of medium                    | -10 °C ... 60 °C                                                   |
| Ambient temperature                      | -10 °C ... 60 °C                                                   |
| Actuating force                          | 14 N                                                               |
| Product weight                           | 156 g                                                              |
| Type of mounting                         | With through-hole                                                  |
| Pneumatic connection 1                   | G1/8                                                               |
| Pneumatic connection 2                   | G1/8                                                               |
| Pneumatic connection 3                   | G1/8                                                               |
| Note on materials                        | RoHS-compliant                                                     |

| Feature          | Value                            |
|------------------|----------------------------------|
| Seals material   | NBR                              |
| Housing material | Wrought aluminum alloy, anodized |
| Lever material   | PA-reinforced                    |