

517 Flexible joint ratchet

reversible, 60 teeth,
handle may be raised or lowered by
approx. 90°. Lockable in following
positions: straight, 30° up,
60° up, 30° down.
Unlocked by depressing button in handle,
registered design.



Code	L mm	b mm	a mm	△△ g	☐
13260001	415	43	26	793	1

522 Ratchet adaptor

reversible, 20 teeth.



Code	L mm	∅ mm	△△ g	☐
13140000	67.5	40	316	1

532 Ratchet

long handle, reversible,
36 teeth.



Code	L mm	b mm	a mm	△△ g	☐
13120010	380	41	21	812	1

501 Speeder brace

working radius 105 mm,
DIN 3122/ISO 3315.



Code	L mm	△△ g	☐
13100010	456	615	5

504 Flexible handle

DIN 3122/ISO 3315.



Code	size	L mm	△△ g	☐
13060011	10	269	515	5
13060012	15	397	700	5
13060013	18	469	779	5

5040 Spare parts set for No 504

for No 504.
Content:
1 Universal Joint
1 Screw
1 Spring Washer



Code	△△ g	☐
96190800	75	1

506 Sliding T-handle

DIN 3122/ISO 3315.



Code	L mm	△△ g	☐
13070000	300	436	5

506QR QuickRelease sliding T-handle




with QuickRelease safety locks.

Code	L mm	△△ g	☐
13071000	300	470	1

509 Extensions


DIN 3123/ISO 3316.



Code	size	L mm	d mm	△△ g	☐
13010001	2	52	23	88	5
13010004	3	75	23.2	120	5
13010002	5	130	23.2	191	5
13010003	10	255	23.2	341	5

509W Extensions with wobble-drive

swivel angle 15° each side,
maximum torque 200 N m.



Code	size	L mm	d mm	△△ g	☐
13010005	2	52	23	80	5
13010006	3	75	23.2	120	5
13010007	5	130	23.2	191	5
13010008	10	255	23.2	341	5

509QR QuickRelease extensions



DIN 3123/ISO 3316.



Code	size	L mm	d mm	△△ g	☐
13011001	2	52	23	90	1
13011004	3	75	23	123	1
13011002	5	130	23	187	1
13011003	10	255	23	341	1