


Feed separator HPVS-10-10-A

Part number: 2095359

FESTO



 [General operating condition](#)

Data sheet

Feature	Value
Stroke	10 mm
Piston diameter	10 mm
Max. replacement accuracy	0.3 mm
Max. stem backlash Sx	0.05 mm
Max. stem backlash Sz	0.03 mm
Max. angular gripper jaw backlash ax	0.12 deg
Max. angular gripper jaw backlash ay	0.2 deg
Max. angular gripper jaw backlash az	0.262 deg
Mounting of external fingers	Through-hole
Cushioning	No cushioning
Mounting position	optional
Mode of operation	Double-acting
Design	Piston rod Non-rotating
Position detection	Via proximity switch
Symbol	00991216
Protection against torque/guide	Square guide
Operating pressure	3 bar ... 8 bar
Advance time	16 ms
Return-stroke time	30 ms
Repetition accuracy	0.05 mm
Operating medium	Compressed air to ISO 8573-1:2010 [7:4:4]
Note on operating and pilot medium	Lubricated operation possible (in which case lubricated operation will always be required)
Corrosion resistance class CRC	2 - Moderate corrosion stress
LABS (PWIS) conformity	VDMA24364-B2-L
Ambient temperature	5 °C ... 60 °C
Max. force on finger Fz static	75 N
Max. torque Mr at finger, static	3 Nm
Max. torque at finger Mx static	3 Nm
Max. torque at finger My static	3 Nm
Theoretical force at 0.6 MPa (6 bar, 87 psi), return stroke	35 N
Theoretical force at 0.6 MPa (6 bar, 87 psi), advance stroke	45 N
Product weight	90 g
Max. mass per external gripper finger	56 g
alternative connections	M3

Feature	Value
Type of mounting	Either: Via female thread and centring sleeve Via through-hole and centring sleeve
Pneumatic connection	M5
Note on materials	RoHS-compliant