



Technical datasheet

4T-L624549/L624510

Single row tapered roller bearings

Tapered roller bearing, pressed steel cage

Visual(s)



Product definition

d	120.65 mm
D	160.34 mm
B	21.43 mm
C	16.67 mm
T	21.43 mm
a	29.6 mm
rs min	1.57 mm
r1s min	1.57 mm
e	0.43
Y2	1.38
Y0	0.76
Mass	1.16 kg
Brand	NTN

Product performance

Dynamic load, C	92.5 kN
Rating life coefficient, A2	1.4
Static load, C0	188 kN
Nlim (oil)	2,700 rpm
Nlim (grease)	2,000 rpm
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.48 Hz
Characteristic rolling element frequency, BSF	18.99 Hz
Characteristic outer ring frequency, BPF0	21.36 Hz
Characteristic inner ring frequency, BPFI	23.64 Hz

Abutment dimensions

ra max	1.5 mm
r1a max	1.5 mm

Calculation factors

Equivalent dynamic radial load

$$P = X.F_r + Y.F_a$$

$F_a / F_r \leq e$		$F_a / F_r > e$	
X	Y	X	Y
1	0	0.4	Y2

Equivalent static radial load

$$P_0 = X_0.F_r + Y_0.F_a$$

X_0	Y_0
0.5	Y0

If $P_0 < F_r$, then use $P_0 = F_r$

The values for e, Y2 and Y0 are shown in the above table