

5 Port Solenoid Valve Base Mounted Series VZ3000

How to Order

Plug-in VZ3 1 4 3 — 5 F Z

Non plug-in VZ3 1 4 0 — 5 L

Type of actuation

1 2 position single
2 2 position double
3 3 position closed center
4 3 position exhaust center
5 3 position pressure center

Body option

0: Individual exhaust for the pilot valve
3: Common exhaust type for main and pilot valve

Rated voltage

1	100 VAC, 50/60 Hz
2	200 VAC, 50/60 Hz
3*	110 VAC, 50/60 Hz
4*	220 VAC, 50/60 Hz
5*	24 VDC
6	12 VDC
9*	Other

* Option

Electrical entry

Grommet	L plug connector	M plug connector	DIN terminal
G: Lead wire length 300 mm	L: With lead wire (Length 300 mm)	M: With lead wire (Length 300 mm)	D: With connector
H: Lead wire length 600 mm	LN: Without lead wire	LO: Without connector	DO: Without connector
		MN: Without lead wire	
		MO: Without connector	

Thread type

Nil	Rc
F	G
N	NPT
T	NPTF

Port size

Nil: Without sub-plate 01: Rc 1/8 With sub-plate

Manual override/Plug-in type

Nil: Non-locking push type B: Locking type B (Slotted) C: Locking type C (Manual)

Manual override/Non plug-in type

Nil: Non-locking push type B: Locking type B (Slotted) C: Locking type C (Manual)

Light/Surge voltage suppressor

Nil	None
Z*	With light/surge voltage suppressor
S	With surge voltage suppressor

* Not available for "GZ", "HZ" and "DOZ"

Note) Please contact SMC in the case of without indicator light.

VK

VZ

VF

VFR

VP4

VZS

VFS

VS4

VQ7

EVS

VFN