

## The Timken Company


4500 Mt Pleasant St. NW N. Canton, OH 44720

**Phone:** (234) 262-3000

E-Mail: <u>CustomerCAD@timken.com</u> • Web site: <u>www.timken.com</u>

## Part Number UCF314, UCF 300 Four-Bolt Flanged Mounted Bearings - Set Screw Locking






## <u>Specifications</u> | <u>Dimensions</u> | <u>Basic Load Ratings</u>


Specifications -				
Ве	earing Number	UC314		
Sh	naft Size d	70 mm		
Lo	ocking Style	Set Screw Locking		
Н	ousing Construction	Four-Bolt Square Flange		

Dimensions –					
	Total Length L	226 mm 8.898 in			
	Housing Width A	61 mm 2.402 in			
	olt Hole Spacing J	178 mm 7.008 in			

Bolt Hole Size N	25 mm 0.984 in
Flange Thickness A1	25 mm 0.984 in
Center of Bearing from Housing End A2	36 mm 1.417 in
Inner Ring Width B	78 mm 3.071 in
Center of Bearing from Bearing End S	33 mm 1.299 in
Dimension A0	81 mm 3.188 in
Bolt Size	M22
Grease Nipple Size	A-R1/8

Basic Load Ratings –						
	Static Load Rating	68200 N 15332 lbf				
	Dynamic Load Rating	104000 N 23380 lbf				





Bearing Number	UC314			
Load Ratings - C <sub>r</sub>	23380	lbf	104000	N
Load Ratings - C <sub>0r</sub>	15332	lbf	68200	N
Weight	22.3	lb	10.1	kg
Bolt Size	M22			

THE TIMKEN COMPANY
NORTH CANTON, OHIO USA

## **UCF314**

UCF 300 Four-Bolt Flanged Mounted Bearings - Set Screw Locking

Every reasonable effort has been made to ensure the accuracy of the information contained in this writing, but no liability is accepted for errors, omissions or for any other reason.

FOR DISCUSSION ONLY