

3505 Special extension

for CROW-FOOT spanner No 3540



Code	L mm	d mm	Δ g	
13210001	120	23.2	186	1

510 Universal joint

DIN 3123/ISO 3316.




Code	L mm	d mm	Δ g	
13020000	71	25	146	5

510QR QuickRelease universal joint



DIN 3123/ISO 3316, with QuickRelease safety locks.



Code	L mm	d mm	Δ g	
13021000	80	25	157	1

513 Adaptor



1/2" socket x 3/8" plug (12.5 x 10),
maximum torque 202 N m,
DIN 3123/ISO 3316,
HPQ high performance steel.



Code	L mm	d mm	Δ g	
13030002	35	22.7	55	5

514 Adaptor



1/2" socket x 3/4" plug (12.5 x 20),
DIN 3123/ISO 3316,
HPQ high performance steel.



Code	L mm	d mm	Δ g	
13030005	44	25	118	5

7789-1 Adaptor



1/2" socket x 1" plug (12.5 x 25 mm),
HPQ high performance steel.



Code	L mm	d mm	Δ g	
58522089	35	36.5	175	1

409M/432M /514M/3 Set adaptors, 3 pieces

1/4" socket x 3/8" plug,
3/8" socket x 1/2" plug,
1/2" socket x 3/4" plug.



Code	Δ g	
96121002	120	1

514M Adaptor

1/2" socket x 3/4" plug
(12.5 x 20 mm).



Code	L mm	ϕ mm	Δ g	
13030010	22	38	50	1

543 Bit holder

○ 5/16" inside hexagon,
DIN 3126 form D 8/ISO 1173 form D 8.
Internal hex drive with a collar-thrust spring
(registered design). Bits are easy to insert,
lock securely in position and can be removed
just as easily; even hex bits with a wide groove
(Type E, DIN 3126/ISO 1173).



Code	L mm	d mm	Δ g	
13180010	38	22	65	5