

TECHNICAL DATASHEET

Updated: 03/06/24

AUTOMATIC LUBRICATOR (6 MONTH)

ltem #	EAN	Product
735601	3660338017322	Automatic Lubricator (6 month)

_

- Description

- Spartex automatic lubricators are designed to lubricate industrial machinery with the right quality of lubricant and at the right time to improve machine reliability & reduce unscheduled shutdowns or production losses whilst enabling workers' safety. Prevents damage & reduces wear.

_

- Application

- Food & beverage industry
- Transport, shipping & traffic engineering
- Fresh & waste water engineering
- Mining & power industry
- Elévation & elevator industry
- Machine & tool industry





Cap colour	Red
Operating time	6 month
Lubricant capacity (cm ³)	120
Discharge capacity at 25°C (g/day)	0,6
Discharge capacity at 35°C (g/day)	0,8
Lubricant	Multi-purpose EP, NLGI 2
Lubricant thickener	Li, Ca
Operating temperature (°C)	-30 to +120
Drop point of lubricant (°C)	155
Lubricant specification	Universal DIN KP2K-30
Delivery of lubricant	Automatic without external power supply
Connecting thread	G ¼″ male

_

- Instructions

- Screw in the starter cap by hand & tighten down firmly (you wil hear the seal break whilst completing this action). Record chage over date. Pre-grease bearing before first installation. Install unit hand tight into grease point

-

Packaging

Dimensons LxWxH (mm)	360 x 300 x 105
Weight (Kg)	6,7
Packing unit	20,0