


## Technical datasheet

### K24X28X17

Needle roller and cage assemblies

Needle roller bearing, cage assembly, steel cage

#### Visual(s)



| Product definition |         |
|--------------------|---------|
| <b>Fw</b>          | 24 mm   |
| <b>Ew</b>          | 28 mm   |
| <b>Bc</b>          | 17 mm   |
| <b>Dw</b>          | 2 mm    |
| <b>Lw</b>          | 13.8 mm |
| <b>Mass</b>        | 0.01 kg |
| <b>Brand</b>       | NTN     |

| Product performance                                  |            |
|------------------------------------------------------|------------|
| <b>Cr</b>                                            | 14.3 kN    |
| <b>C0r</b>                                           | 23.9 kN    |
| <b>Nlim (grease)</b>                                 | 11,000 rpm |
| <b>Nlim (oil)</b>                                    | 17,000 rpm |
| <b>Min operating temperature, Tmin</b>               | -20 °C     |
| <b>Max operating temperature, Tmax</b>               | 120 °C     |
| <b>Characteristic cage frequency, FTF</b>            | 0.46 Hz    |
| <b>Characteristic rolling element frequency, BSF</b> | 12.92 Hz   |
| <b>Characteristic outer ring frequency, BPF0</b>     | 10.15 Hz   |
| <b>Characteristic inner ring frequency, BPF1</b>     | 11.85 Hz   |

| Abutment dimensions |       |
|---------------------|-------|
| <b>b</b>            | 17 mm |