



# Solenoid valve VSVA-B-P53E-H-A2-1R2L

Part number: 534779

FESTO



 [General operating condition](#)

## Data sheet

| Feature                                      | Value                                                                |
|----------------------------------------------|----------------------------------------------------------------------|
| Valve function                               | 5/3 exhausted                                                        |
| Type of actuation                            | Electric                                                             |
| Construction width                           | 18 mm                                                                |
| Standard nominal flow rate                   | 450 l/min                                                            |
| pneumatic working port                       | Sub-base size 18 mm to ISO 15407-1<br>Sub-base size 02 to VDMA 24563 |
| Operating voltage                            | 24V DC                                                               |
| Operating pressure                           | 0.3 MPa ... 0.8 MPa                                                  |
| Operating pressure                           | 3 bar ... 8 bar                                                      |
| Design                                       | Piston gate valve                                                    |
| Type of reset                                | Mechanical spring                                                    |
| Approval                                     | C-Tick<br>c UL us - Recognized (OL)                                  |
| CE mark (see declaration of conformity)      | To EU EMC Directive                                                  |
| CE marking (see declaration of conformity)   | To UK instructions for EMC<br>To UK RoHS instructions                |
| Degree of protection                         | IP65                                                                 |
| Nominal size                                 | 5 mm                                                                 |
| Exhaust-air function                         | With flow control option                                             |
| Sealing principle                            | Soft                                                                 |
| Mounting position                            | optional                                                             |
| Conforms to standard                         | ISO 15407-1<br>VDMA 24563                                            |
| Manual override                              | Non-detenting                                                        |
| Type of piloting                             | Pilot actuated                                                       |
| Pilot air supply                             | Internal                                                             |
| Flow direction                               | Non-reversible                                                       |
| Symbol                                       | 00991082                                                             |
| lap                                          | Overlap                                                              |
| Reverse polarity protection                  | For all electrical connections                                       |
| Additional functions                         | Holding current reduction<br>Safety shut-off                         |
| Signal status display                        | LED                                                                  |
| Flow rate of valve                           | 650 l/min                                                            |
| Flow rate of valve on individual sub-base    | 500 l/min                                                            |
| Flow rate of pneumatically interlinked valve | 450 l/min                                                            |
| Switching time off                           | 36 ms                                                                |

| Feature                                        | Value                                                                                      |
|------------------------------------------------|--------------------------------------------------------------------------------------------|
| Switching time on                              | 15 ms                                                                                      |
| Operational voltage range DC                   | 21.6 V ... 26.4 V                                                                          |
| Duty cycle                                     | 100%                                                                                       |
| Max. positive test pulse with 0 signal         | 500 µs                                                                                     |
| Max. negative test pulse with 1 signal         | 500 µs                                                                                     |
| Characteristic coil data                       | 24 V DC: low-current phase 1.0 W, high-current phase 2.4 W                                 |
| Operating medium                               | Compressed air to ISO 8573-1:2010 [7:4:4]                                                  |
| Note on operating and pilot medium             | Lubricated operation possible (in which case lubricated operation will always be required) |
| Vibration resistance                           | Transport application test with severity level 2 to FN 942017-4 and EN 60068-2-6           |
| Shock resistance                               | Shock test with severity level 2 to FN 942017-5 and EN 60068-2-27                          |
| Corrosion resistance class CRC                 | 2 - Moderate corrosion stress                                                              |
| LABS (PWIS) conformity                         | VDMA24364-B1/B2-L                                                                          |
| Media temperature                              | -5 °C ... 50 °C                                                                            |
| Relative air humidity                          | 0 - 90%                                                                                    |
| Protection against direct and indirect contact | PELV                                                                                       |
| Ambient temperature                            | -5 °C ... 50 °C                                                                            |
| Max. tightening torque for valve mounting      | 0.9 Nm ... 1.1 Nm                                                                          |
| Product weight                                 | 140 g                                                                                      |
| Electrical connection                          | 4-pin<br>M8x1<br>Central plug<br>Round design                                              |
| Type of mounting                               | On sub-base                                                                                |
| Note on materials                              | RoHS-compliant                                                                             |