



## Housing units RMEY60-XL-N (Series RMEY)

four-bolt flanged housing units, cast iron, centring spigot, grub screws in inner ring, R seals

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue ordering system ([https://www.schaeffler.de/content.schaeffler.de/en/news\\_media/index.jsp](https://www.schaeffler.de/content.schaeffler.de/en/news_media/index.jsp)) or by telephone on +49 (91 32) 82 - 28 97.

d	60 mm
H	195 mm
B	65,1 mm
A	29 mm
A <sub>1</sub>	16 mm
A <sub>2</sub>	1 mm
J	160 mm
N	18 mm
Q	M6
S	3 mm
U	38,7 mm
Z	135 mm    Tolerance: h8

m	3,71 kg	Mass
C <sub>r</sub>	56000 N	Basic dynamic load rating, radial
C <sub>0r</sub>	36000 N	Basic static load rating, radial
	ME12	Designation of housing
	GYE60-XL-KRR-B	Designation of bearing
	KASK12	Bearing end cap, closed design. To be ordered separately.
		Slot for bearing end cap



