


# Flat cylinder DZF-18-25-P-A

Part number: 164016

FESTO



 [General operating condition](#)

## Data sheet

| Feature                                                      | Value                                                                                      |
|--------------------------------------------------------------|--------------------------------------------------------------------------------------------|
| Stroke                                                       | 25 mm                                                                                      |
| Piston diameter                                              | 18 mm<br>Equivalent diameter                                                               |
| Torsional backlash at piston rod +/-                         | 1.2 deg                                                                                    |
| Cushioning                                                   | Elastic cushioning rings/plates at both ends                                               |
| Mounting position                                            | optional                                                                                   |
| Mode of operation                                            | Double-acting                                                                              |
| Design                                                       | Piston<br>Piston rod                                                                       |
| Position detection                                           | Via proximity switch                                                                       |
| Symbol                                                       | 00991217                                                                                   |
| Protection against torque/guide                              | Oval piston                                                                                |
| Operating pressure                                           | 0.1 MPa ... 1 MPa                                                                          |
| Operating pressure                                           | 1 bar ... 10 bar                                                                           |
| Operating medium                                             | Compressed air to ISO 8573-1:2010 [7:4:4]                                                  |
| Note on operating and pilot medium                           | Lubricated operation possible (in which case lubricated operation will always be required) |
| Corrosion resistance class CRC                               | 2 - Moderate corrosion stress                                                              |
| LABS (PWIS) conformity                                       | VDMA24364-B1/B2-L                                                                          |
| Ambient temperature                                          | -20 °C ... 80 °C                                                                           |
| Max. torque for protection against torsion                   | 0.2 Nm                                                                                     |
| Theoretical force at 0.6 MPa (6 bar, 87 psi), return stroke  | 123 N                                                                                      |
| Theoretical force at 0.6 MPa (6 bar, 87 psi), advance stroke | 153 N                                                                                      |
| Moving mass for 0 mm stroke                                  | 24 g                                                                                       |
| Additional moving mass per 10 mm stroke                      | 4 g                                                                                        |
| Additional weight per 10 mm stroke                           | 13 g                                                                                       |
| Basic weight for 0 mm stroke                                 | 107 g                                                                                      |
| Type of mounting                                             | Either:<br>Via female thread<br>With accessories                                           |
| Pneumatic connection                                         | M5                                                                                         |
| Material cover                                               | Wrought aluminium alloy                                                                    |
| Material seals                                               | NBR<br>TPE-U(PU)                                                                           |
| Material housing                                             | Aluminium<br>Smooth anodised                                                               |
| Material piston rod                                          | High-alloy stainless steel                                                                 |