

## TWO POLE VOLTAGE TESTER

### Description

Standard: EN 61243-3:2014 – CAT IV 1000V Sturdy and safe device.  
 Convenient one-handed handling.  
 High degree of security: CAT IV, 1000V.  
 Also suitable for measurements on hybrid and electric vehicles, as well as photovoltaic installations.  
 Batteries included.  
 Indicator: LED Optics  
 Measuring range selection: automatic Voltage range: 6 – 1000V AC , 6 – 1000V DC  
 Overvoltage category: CAT IV 1000V Continuity check: 0-50 K $\Omega$  with optical/audible signal  
 Phase indicator: > 100V AC  
 Phase 1 Pole control: YES  
 Bipolar control of the rotating magnetic field: YES  
 Control Test FI/RCD 30mA at 230v AC using 2 keys  
 Diode testing: YES  
 Polarity: Yes (+/-LED) Indicator: Optical, sound and vibrating PELV  
 Measuring point illumination: White LED  
 Automatic stop: YES  
 Guard: IP65 Dimensions: 300 x 75 x 20 mm  
 Weight: 270 g  
 Power supply: 2 x 1.5v AAA (voltage display possible without batteries)  
**WARRANTY 2 YEARS**



### Characteristics

Ref.	EAN	Measurement range	Category of preload	Display
860231	3660338151910	6 - 1000V CA, 6 - 1000V CC	CAT IV 1000V	Bright