



A

“V” Series Basic Modules Size 2 (Without Pneumatic Connectors)



Single Solenoid



Double Solenoid

Size 2 Electro-Pneumatic Island Valve Modules, 24VDC

4-Way / 2-Position / Single Valve

	Solenoid	Weight	Part Number
	Single Solenoid (Monostable)	3.53 oz	P2M2V4ES2CV
	Double Solenoid (Bistable)	3.88 oz	P2M2V4EE2CV

3-Way / 2-Position / Dual Valve

	Solenoid	Weight	Part Number
	Double Solenoid NC + NC with Exhaust Check	4.06 oz	P2M2VDEE2CV
	Double Solenoid NO + NO with Exhaust Check	4.06 oz	P2M2VCEE2CV
	Double Solenoid NC + NO with Exhaust Check	4.06 oz	P2M2VEEE2CV
	Single Solenoid NC with Exhaust Check	3.88 oz	P2M2V3ES2CV
	Center Exhaust = dual 3/2 NC + NC without Exhaust Check	4.06 oz	P2M2VGEE2CV

Pneumatic Connectors for Size 2 Modules



PMDYY2



MMDVA2



HMDXX2



FMD09-2



CMD13-2

		Elbow Version		Straight Version	
		Weight (oz)	Order Code	Weight (oz)	Order Code
Tube Push-in Connector	6mm OD	0.18	CMD06-2	0.11	FMD06-2
	1/4" OD	0.18	CMD07-2B	0.11	FMD07-2B
	8mm OD	0.21	CMD08-2	0.14	FMD08-2
	3/8" OD	0.21	CMD09-2B	0.14	FMD09-2B
	10mm OD	0.25	CMD10-2	0.18	FMD10-2
	12mm OD	0.28	CMD12-2	0.21	FMD12-2
	1/2" OD	—	—	0.21	FMD13-2B
Muffler for Exhaust Port	—	—	—	0.11	MMDVA2
Plug	—	—	—	0.18	PMDYY2
Double Male Union (For Peripheral Valve Modules)	—	—	—	0.28	HMDXX2

Note: 85 Durometer minimum for pneumatic connectors.

Note: Bold Options Standard