

## MULTIMETER

### Description

Standard IEC/ EN 61010-1, IEC/EN 61010-2-033 - CAT III 600V Multimeter with a easily-readable backlit LCD display.

Measurement lines, carrying case, temperature probe, batteries included.

Indicator: 40mm illuminated LCD Diode testing: YES

Continuity tester: YES

Temperature measurement: -20 -1000°C with K-type probe

Maximum input voltage: 600V AC/DC

Input impedance > 7.5 MΩ, Typ. 10MΩ (AC V & DC V) Fluctuation margin of the alternative voltage: 50 - 400Hz

Frequency measuring range: 10 Hz – 10 MHz

Capacity Measuring range: Up to 20 μF 600mA (self-adjusting) 10A/690 V circuit breaker (FAST) Operating temperature range: 0 - 40°C (32 - 104°F) Storage temperature range: -

10 - 50°C (14 - 122°F) Category of preload: CAT III 600V

Dimensions: 183 x 95 x 50 mm

Weight: 410 g (with batteries)

Power supply 2 x 1.5 V AA

2-YEAR WARRANTY



### Characteristics

| Ref.   | EAN           | Measurement range | Category of preload |
|--------|---------------|-------------------|---------------------|
| 873171 | 3660338268090 | 10 Hz – 10 MHz    | CAT III 600V        |