



Accessories

Electrode needle cleaning kit	IZS30-M2
Remote control	IZS41-RC
Transition wiring cable (2 m)	IZS41-CF02
High speed de-ionizing cartridge (tungsten)	IZS40-NT
Energy saving - type de-ionizing cartridge (tungsten)	IZS40-NJ
Electrode cartridge drop prevention cover for 3 electrodes	IZS40-E3
Electrode cartridge drop prevention cover for 4 electrodes	IZS40-E4
Electrode cartridge drop prevention cover for 5 electrodes	IZS40-E5
AC Adapter for IZS40	IZF10-CG2EU
AC Adapter for IZS41/42	IZS41-CG2EU
End bracket	IZS40-BE
Intermediate bracket	IZS40-BM
Feedback sensor	IZS31-DF
Auto balance sensor	IZS31-DG

Series IZN10

Nozzle Type Ionizer



IZN10



IZN10-X367

Efficient local static removal

- Different nozzles to adapt several applications, available either as IZN10 (standard type) and IZN10-X367 (with right angles and 360° rotation):
Energy saving static electricity elimination nozzle.
High flow static electricity elimination nozzle.
- Ion balance: ± 15 V.
- Compact and slim design.
- With built-in power supply substrate.
- Easy maintenance: electrode needle contamination detector with easy replacement of the cartridge.
- Mounting variations: direct mount, bracket mount.
- External switch input function (2 inputs). Switch output: PNP/NPN.

Part number	Nozzle type	Port size	Output specification
IZN10-01P06	Energy saving static electricity elimination nozzle	Ø 6 (metric size)	PNP
IZN10-02P06	High flow rate nozzle		
IZN10-11P06	Rc 1/8 female threads for piping		

* Incl. 3 m power supply cable.

* NPN option available upon request

Accessories

L Bracket	IZN10-B1
Pivoting bracket	IZN10-B2
Din rail mounting bracket	IZN10-B3
Power supply cable (3 m)	IZN10-CP
Power supply cable (10 m)	IZN10-CPZ
Electrode needle assembly	IZN10-NT
Circular diffusion nozzle	IZN10-G-X198
Flat diffusion nozzle	IZN10-G-X199
Bar nozzle (straight type), bar length 400 mm	IZN10-G-400-X216
Bar nozzle (straight type), bar length 600 mm	IZN10-G-600-X216