

## **The Timken Company**


4500 Mt Pleasant St. NW N. Canton, OH 44720

**Phone:** (234) 262-3000

E-Mail: <u>CustomerCAD@timken.com</u> • Web site: <u>www.timken.com</u>

## Part Number UCF318, UCF 300 Four-Bolt Flanged Mounted Bearings - Set Screw Locking






## <u>Specifications</u> | <u>Dimensions</u> | <u>Basic Load Ratings</u>


Specifications –					
	Bearing Number	UC318			
	Shaft Size d	90 mm			
	Locking Style	Set Screw Locking			
	Housing Construction	Four-Bolt Square Flange			

Dimensions -						
	Total Length L	280 mm 11.024 in				
	Housing Width A	76 mm 2.992 in				
	olt Hole Spacing J	216 mm 8.504 in				

Bolt Hole Size N	35 mm 1.378 in
Flange Thickness A1	30 mm 1.181 in
Center of Bearing from Housing End A2	44 mm 1.732 in
Inner Ring Width B	96 mm 3.780 in
Center of Bearing from Bearing End S	40 mm 1.575 in
Dimension A0	100 mm 3.938 in
Bolt Size	M30
Grease Nipple Size	A-R1/8

Basic Load Ratings –						
	Static Load Rating	107000 N 24055 lbf				
	Dynamic Load Rating	143000 N 32148 lbf				





Bearing Number	UC318			
Load Ratings - C <sub>r</sub>	32148	lbf	143000	N
Load Ratings - C <sub>0r</sub>	24055	lbf	107000	N
Weight	41.7	lb	18.9	kg
Bolt Size	M30			

THE TIMKEN COMPANY
NORTH CANTON, OHIO USA

## **UCF318**

UCF 300 Four-Bolt Flanged Mounted Bearings - Set Screw Locking

Every reasonable effort has been made to ensure the accuracy of the information contained in this writing, but no liability is accepted for errors, omissions or for any other reason.

FOR DISCUSSION ONLY