

### PVC adhesive marking tape 50 mm x 33 m

#Item	EAN	Color
<b>886641</b>	3660338400476	Black/Yellow
<b>886642</b>	3660338400483	Yellow
<b>886643</b>	3660338400490	Blue
<b>886644</b>	3660338400506	White
<b>886645</b>	3660338400513	Black
<b>886646</b>	3660338400520	Red
<b>886647</b>	3660338400537	Green



### Description

0.16mm premium quality soft PVC tape, which uses an aggressive pressure sensitive rubberbased adhesive system. It combines excellent mechanical strength, easy transversal tearability and abrasion resistance with excellent conformability for use in lane marking and flooring applications.

### Applications

Colour coding. Flooring and lane marking. General splicing.

### Characteristics

Technical attribute	Nominal value	Test Method
Width	50 mm	
Length	33 m	
Total Thickness	0,16 mm	CEI EN 60454
Tensile Strength	25 N/cm	CEI EN 60454
Elongation at Break	150%	CEI EN 60454
Adhesion to backing	1,5 N/cm	CEI EN 60454
Adhesion to Steel	1,5 N/cm	CEI EN 60454

### Instructions & storage

Use within 24 months of receipt. The tape should be applied with sufficient pressure to ensure an optimum bonding and prevent ageing effects. Surfaces should be clean, dry and free of dust, grease, oil or other contaminants. Rolls should be stored at on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. The storage temperature should be between +10°C and +25°C.

### Certifications

Conforms to European Directive 2000/53 EC (lead, chromium VI, mercury, cadmium free).

### Packaging

- 1 unit