



Black Cable Ties

Order Codes

CODE	SIZE (mm)	MAX. BUNDLE (mm)	MIN. TENSILE STRENGTH (kg)
650002	100 x 2.5	22	8 kg
650004	140 x 3.6	33	8 kg
650005	160 x 2.5	40	8 kg
650006	200 x 4.8	38	22 kg
650007	200 x 2.5	53	8 kg
650008	200 x 3.6	53	18 kg
65009	200 x 4.8	50	22 kg
650010	300 x 3.6	76	18 kg
650011	300 x 4.8	76	22 kg
650012	300 x 7.6	76	55 kg
650013	370 x 4.8	102	22 kg
650014	370 x 7.6	102	55 kg
650015	450 x 9.0	120	80 kg
650016	526 x 9.0	160	80 kg
650026	580 x 13.2	152	114 kg
650020	650 x 9.0	187	80 kg
650017	780 x 9.0	228	80 kg
650022	1000 x 9.0	295	80 kg

Features & Benefits

Crimp-Pak Cable Ties are produced to comply with BS EN50146:2000 requirements and are supplied in accordance with ISO 9001 accreditation. All have an operating temperature range of -40°C to +85°C and are primarily manufactured from virgin nylon 66.

Virgin Nylon 66

ISO9001

Comply with BS EN50146:2000

Halogen free

Natural Cable Ties

Specification

Material: High quality virgin nylon 66 halogen free
Strength: Tensile strength to UL Specification
Operating Temperature: -40°C - +85°C
Flame Resistance: UL94V2
UL: Approved
Pack Qty: 100

Order Codes

CODE	SIZE (mm)	MAX. BUNDLE (mm)	MIN. TENSILE STRENGTH (kg)
651001	80 x 2.4	15	8 kg
651020	100 x 2.4	22	8 kg
651002	100 x 2.5	33	8 kg
651004	140 x 3.6	40	18 kg
651005	160 x 2.5	38	8kg
651006	160 x 4.8	53	22 kg
651007	200 x 2.5	53	8 kg
651008	200 x 3.6	50	18 kg
651009	200 x 4.8	76	22 kg
651010	300 x 3.6	76	18 kg
651011	300 x 4.8	76	22 kg
651012	300 x 7.6	102	55 kg
651013	370 x 4.8	102	22 kg
651014	370 x 7.6	120	55 kg
651015	450 x 9.0	140	80 kg
651016	530 x 9.0	152	80 kg
651026	650 x 9.0	228	80 kg
651017	780 x 9.0	295	80 kg
651022	940 x 9.0	295	80 kg

