

Turning Motion Technology

Series C9000

Nominal Diameter
5,5

ISO B



Technical Data

max. Working Pressure 16 bar

Temperature Range -20°C up to +60°C (NBR)

Flow rate 1.250 l/min.
At input pressure 6 bar, pressure drop 0.6 bar

Material
Coupling: Technical polymer, Nickel plated brass
Plug: Nickel plated steel
Seal: NBR

Coupler - Male Thread

	C	Part Number
	G 1/4	9401U06 13
	R 1/4	9405U06 13
	G 3/8	9401U06 17
	R 3/8	9405U06 17
	G 1/2	9401U08 21
	R 1/2	9405U06 21

Plug - Male Thread

	C	Part Number
	G 1/4	9087U06 13
	G 3/8	9087U06 17
	G 1/2	9087U06 21

Coupler - Female Thread

	C	Part Number
	G 1/4	9414U06 13
	G 3/8	9414U06 17
	G 1/2	9414U06 21

Plug - Female Thread

	C	Part Number
	G 1/4	9086 23 13
	G 3/8	9086 23 17
	G 1/2	9086 23 21

Coupler - Hose Barb

	I.D. Hose	Part Number
	6 mm	9421U06 06
	8 mm	9421U06 08
	10 mm	9421U06 10

Plug - Hose Barb

	I.D. Hose	Part Number
	6 mm	9094U06 06
	8 mm	9094U06 08
	10 mm	9094U06 10