


The Timken Company

4500 Mt Pleasant St. NW


N. Canton, OH 44720

Phone: (234) 262-3000

E-Mail: CustomerCAD@timken.com • **Web site:** www.timken.com

Part Number LM48548 - LM48510, Tapered Roller Bearings - TS (Tapered Single) Imperial

This is the most basic and most widely used type of tapered roller bearing. It consists of two main separable parts: the cone (inner ring) assembly and the cup (outer ring). It is typically mounted in opposing pairs on a shaft.



[Specifications](#) | [Dimensions](#) | [Abutment and Fillet Dimensions](#) | [Basic Load Ratings](#) | [Factors](#)

Specifications

Series	LM48500
Cone Part Number	LM48548
Cup Part Number	LM48510
Design Unit	Inch
Cage Material	Stamped Steel
Related Assembly Number(s)	LM48548-90299 LM48548-902C6

Dimensions



- Bore

1 3/8 in

34.925 mm

D - Cup Outer Diameter	2.5625 in 65.088 mm
B - Cone Width	0.7200 in 18.288 mm
C - Cup Width	0.5500 in 13.970 mm
T - Bearing Width	0.71 in 18.034 mm

Abutment and Fillet Dimensions

R - Cone Backface "To Clear" Radius¹	0.14 in 3.600 mm
r - Cup Backface "To Clear" Radius²	0.050 in 1.27 mm
da - Cone Frontface Backing Diameter	1.63 in 41.5 mm
db - Cone Backface Backing Diameter	1.89 in 48 mm
Da - Cup Frontface Backing Diameter	2.44 in 61.00 mm
Db - Cup Backface Backing Diameter	2.28 in 57.91 mm
Ab - Cage-Cone Frontface Clearance	0.08 in 2 mm
Aa - Cage-Cone Backface Clearance	0.01 in 0.3 mm
a - Effective Center Location³	-0.15 in -3.8 mm

Basic Load Ratings

C90 - Dynamic Radial Rating (90 million revolutions)⁴	3760 lbf 16700 N
C1 - Dynamic Radial Rating (1 million revolutions)⁵	14500 lbf 64600 N
C0 - Static Radial Rating	14200 lbf 63100 N
C_{a90} - Dynamic Thrust Rating (90 million revolutions)⁶	2430 lbf 10800 N

Factors

K - Factor⁷	1.55
e - ISO Factor⁸	0.38
Y - ISO Factor⁹	1.59
C_g - Geometry Factor¹⁰	0.0666

¹ These maximum fillet radii will be cleared by the bearing corners.

² These maximum fillet radii will be cleared by the bearing corners.

³ Negative value indicates effective center inside cone backface.

⁴ Based on 90×10^6 revolutions L_{10} life, for The Timken Company life calculation method. C_{90} and C_{a90} are radial and thrust values.

⁵ Based on 1×10^6 revolutions L_{10} life, for the ISO life calculation method.


⁶ Based on 90×10^6 revolutions L_{10} life, for The Timken Company life calculation method. C_{90} and C_{a90} are radial and thrust values for a single-row, $C_{90(2)}$ is the two-row radial value.

⁷ These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.

⁸ These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.

⁹ These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.

¹⁰ Geometry constant for Lubrication Life Adjustment Factor a_3 .



IMPERIAL UNITS

ISO Factor - e 0.38
 ISO Factor - Y 1.59
 Bearing Weight 0.5 lb
 Number of Rollers Per Row 19
 Effective Center Location -0.15 inch

TIMKEN®

THE TIMKEN COMPANY
 NORTH CANTON, OHIO USA

LM48548 - LM48510
 Tapered Roller Bearings - TS (Tapered Single)
 Imperial

K Factor 1.55
 Dynamic Radial Rating - C90 3760 lbf
 Dynamic Thrust Rating - Ca90 2430 lbf
 Static Radial Rating - C0 14200 lbf
 Dynamic Radial Rating - C1 14500 lbf

Every reasonable effort has been made to ensure the accuracy of the information contained in this writing, but no liability is accepted for errors, omissions or for any other reason.

FOR DISCUSSION ONLY