

Spline Micrometers

SERIES 331, 111

FEATURES

- IP65 water/dust protection (Series 331).
- The anvil and spindle have a small diameter for measuring splined shafts, slots, and keyways.
- Non-slip grip finish (digital models)
- With ratchet stop for constant force.
- With SPC output (Series 331).
- With a standard bar except 0-1" and 0-25mm model.
- Supplied in fitted plastic case.




SPECIFICATIONS

Metric		Digital model			
Range	Resolution	Order No.	Accuracy	Remarks	Mass (g)
0 - 25mm	0.001mm	331-251-30	±2μm	Type A	330
		331-261-30	±2μm	Type B	330
25 - 50mm	0.001mm	331-252-30	±2μm	Type A	470
		331-262-30	±2μm	Type B	470
50 - 75mm	0.001mm	331-253-30	±2μm	Type A	625
		331-263-30	±2μm	Type B	625
75 - 100mm	0.001mm	331-254-30	±3μm	Type A	565
		331-264-30	±3μm	Type B	565

Metric		Digital model			
Range	Graduation	Order No.	Accuracy	Remarks	Mass (g)
0 - 25mm	0.01mm	111-115	±3μm	Type A	205
		111-215	±3μm	Type B	205
25 - 50mm	0.01mm	111-116	±3μm	Type A	305
		111-117	±3μm	Type A	370
50 - 75mm	0.01mm	111-118	±4μm	Type A	500
		111-119	±4μm	Type A	655
125 - 150mm	0.01mm	111-120	±4μm	Type A	710
		111-121	±5μm	Type A	900
150 - 200mm	0.01mm	111-122	±5μm	Type A	1040

DIMENSIONS



Technical Data

Accuracy: Refer to the list of specifications
 Resolution*: .00005" / 0.001mm or 0.001mm
 Graduation*: .0001" or 0.01mm, .001"
 Flatness: .000012" / 0.3μm
 Parallelism: (2+R/100)μm, R=max. range (mm)
 [.00008" + .00004" (L/4")]
 L = max. range (inch)
 Measuring faces: Carbide tipped
 Display*: LCD
 Battery*: SR44 (1 pc.), **938882**
 Battery life*: Approx. 2.4 years under normal use
 Dust/Water protection level*: IP65
 *Digital models **Analog models

Function of Digital Model

Origin-set, Zero-setting, Data hold, Data output, inch/mm conversion (on inch/metric models only)
 Function lock
 Alarm: Low voltage, Counting value composition error

Optional Accessories for Digital Model

05CZA662: SPC cable with data switch (40" / 1m)
05CZA663: SPC cable with data switch (80" / 2m)

Inch/Metric		Digital model			
Range	Resolution	Order No.	Accuracy	Remarks	Mass (g)
0 - 1" / 0 - 25.4mm	.00005" / 0.001mm	331-351-30	±.0001"	Type A	330
		331-361-30	±.0001"	Type B	330
1 - 2" / 25.4-50.8mm	.00005" / 0.001mm	331-352-30	±.0001"	Type A	470
		331-362-30	±.0001"	Type B	470
2 - 3" / 50.8-76.2mm	.00005" / 0.001mm	331-353-30	±.0001"	Type A	625
		331-363-30	±.0001"	Type B	625
3 - 4" / 76.2-101.6mm	.00005" / 0.001mm	331-354-30	±.00015"	Type A	565
		331-364-30	±.00015"	Type B	565

Inch		Digital model			
Range	Graduation	Order No.	Accuracy	Remarks	Mass (g)
0 - 1"	.0001"	111-166*	±.00015"	Type A	205

*.0001" reading is obtained with vernier.

