

Compact Guide Cylinder

Series *MGQ*

ø12, ø16, ø20, ø25, ø32, ø40, ø50, ø63, ø80, ø100

How to Order

Compact Guide Cylinder

MGQ M 25 — **30** — **M9BW** —

• **Made to Order**
(Refer to page 339 for details.)

Compact Guide Cylinder •

• **Bearing type**

M	Slide bearing
L	Ball bushing bearing

• **Bore size**

12	12 mm	40	40 mm
16	16 mm	50	50 mm
20	20 mm	63	63 mm
25	25 mm	80	80 mm
32	32 mm	100	100 mm

• **Number of auto switches**

Nil	2 pcs.
S	1 pc.
n	n pcs.

• **Auto switch**

Nil	Without auto switch (Built-in magnet)
------------	--

* For the applicable auto switch model, refer to the table below.

• **Cylinder stroke (mm)**

Refer to "Standard Stroke" on page 339.

• **Thread type**

Nil	M5 x 0.8	ø12, ø16
TN	Rc	
TF	NPT	ø20 to ø100
	G	

Applicable Auto Switch/Refer to pages 1719 to 1827 for further information on auto switches.

Type	Special function	Electrical entry	Indicator light	Wiring (Output)	Load voltage		Auto switch model		Lead wire length (m)				Pre-wired connector	Applicable load			
					DC	AC	Perpendicular	In-line	0.5 (Nil)	1 (M)	3 (L)	5 (Z)					
Solid state switch	—	Grommet	Yes	3-wire (NPN)	24 V	5 V, 12 V	—	M9NV	M9N	●	●	●	○	○	Relay, PLC		
	3-wire (PNP)					M9PV		M9P	●	●	●	○	○	IC circuit			
	2-wire			12 V		M9BV		M9B	●	●	●	○	○	—			
	3-wire (NPN)			5 V, 12 V		M9NWV		M9NW	●	●	●	○	○	IC circuit			
	3-wire (PNP)					M9PWV		M9PW	●	●	●	○	○	IC circuit			
	2-wire			12 V		M9BWV		M9BW	●	●	●	○	○	—			
	3-wire (NPN)			5 V, 12 V		M9NAV **		M9NA **	○	○	●	○	○	IC circuit			
	3-wire (PNP)					M9PAV **		M9PA **	○	○	●	○	○	IC circuit			
	Water resistant (2-color indication)			2-wire	12 V		M9BAV **	M9BA **	○	○	●	○	○	—			
Reed switch	—	Grommet	Yes	3-wire (NPN equivalent)	—	5 V	—	A96V	A96	●	—	●	—	—	IC circuit	—	
				No	2-wire	24 V	12 V	100 V	A93V	A93	●	—	●	—	—	—	—
			100 V or less					A90V	A90	●	—	●	—	—	—	—	IC circuit

** Water resistant type auto switches can be mounted on the above models, but in such case SMC cannot guarantee water resistance. Consult with SMC regarding water resistant types with the above model numbers.

* Lead wire length symbols: 0.5 m Nil (Example) M9NW
1 m M (Example) M9NWM
3 m L (Example) M9NWL
5 m Z (Example) M9NWZ

* Solid state auto switches marked with "○" are produced upon receipt of order.

* Since there are other applicable auto switches than listed, refer to page 351 for details.
* For details about auto switches with pre-wired connector, refer to pages 1784 and 1785.
* Auto switches are shipped together (not assembled).

Air cylinder integrated with guide has achieved anti-lateral load and high non-rotating accuracy.

Space-saving and compact design

Suitable as stoppers or lifters in conveyor line

2 types of guide rod bearing are available depending upon the application

Slide bearing/Ball bushing bearing



Made to Order Specifications
(For details, refer to pages 1829 to 2021.)

Symbol	Specifications
—XA□	Change of rod end shape
—XB6	Heat resistant cylinder (−10 to 150°C)
—XB9	Low speed cylinder (10 to 50 mm/s)
—XB10	Intermediate stroke (Using exclusive body)
—XC22	Fluororubber seals
—XC56	With knock pin holes
—XC79	Machining tapped hole, drilled hole, and pin hole additionally
—X168	Helical insert thread
—X367	Bottom mounting style
—X399	Long bushing type
—X563	With anti-strong magnetic field switch (D-P4DW)

Specifications

Bearing type	Slide bearing		Ball bushing bearing
Model	MGQM		MGQL
Bore size (mm)	12, 16, 20, 25, 32, 40, 50, 63, 80, 100		
Action	Double acting		
Fluid	Air		
Proof pressure	1.5 MPa		
Max. operating pressure	1.0 MPa		
Min. operating pressure	ø12, ø16	0.12 MPa	
	ø20 to ø100	0.1 MPa	
Ambient and fluid temperature	−10 to 60°C (No freezing)		
Piston speed	ø12 to ø63	50 to 500 mm/s	
	ø80, ø100	50 to 400 mm/s	
Cushion	Rubber bumper on both ends		
Lubrication	Non-lube		
Stroke length tolerance	$^{+1.5}_0$ mm		

Standard Stroke

Model	Standard stroke (mm)	Intermediate stroke (mm)
MGQ ^M 12, 16	10, 20, 30, 40, 50, 75, 100	As for the intermediate strokes other than the standard strokes at left are manufactured by means of installing a spacer. ø12 to ø32 Stroke available by the 1 stroke interval ø40 to ø100 Stroke available by the 5 stroke interval (Example) 1. For MGQM20-21 st, MGQM20-30 st is provided with a 5 mm + 4 mm ≤ 9 mm width spacer. 2. For MGQM50-40 st, MGQM50-50 st is provided with a 10 mm width spacer.
MGQ ^M 20, 25	20, 30, 40, 50, 75, 100 125, 150, 175, 200	
MGQ ^M 32, 40 50, 63 80, 100	25, 50, 75, 100, 125 150, 175, 200	

Theoretical Output

Bore size (mm)	Rod size (mm)	Operating direction	Piston area (mm ²)	Operating pressure (MPa)										
				0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.0		
12	6	OUT	113	23	34	45	57	68	79	90	102	113		
		IN	85	17	26	34	43	51	60	68	77	85		
16	8	OUT	201	40	60	80	101	121	141	161	181	201		
		IN	151	30	45	60	76	91	106	121	136	151		
20	10	OUT	314	63	94	126	157	188	220	251	283	314		
		IN	236	47	71	94	118	142	165	189	212	236		
25	12	OUT	491	98	147	196	246	295	344	393	442	491		
		IN	378	76	113	151	189	227	265	302	340	378		
32	16	OUT	804	161	241	322	402	482	563	643	724	804		
		IN	603	121	181	241	302	362	422	482	543	603		
40	16	OUT	1257	251	377	503	629	754	880	1006	1131	1257		
		IN	1056	211	317	422	528	634	739	845	950	1056		
50	20	OUT	1963	393	589	785	982	1178	1374	1570	1767	1963		
		IN	1649	330	495	660	825	990	1154	1319	1484	1649		
63	20	OUT	3117	623	935	1247	1559	1870	2182	2494	2805	3117		
		IN	2803	561	841	1121	1402	1682	1962	2242	2523	2803		
80	25	OUT	5027	1005	1508	2011	2514	3016	3519	4022	4524	5027		
		IN	4536	907	1361	1814	2268	2722	3175	3629	4082	4536		
100	30	OUT	7854	1571	2356	3142	3927	4712	5498	6283	7069	7854		
		IN	7147	1429	2144	2859	3574	4288	5003	5718	6432	7147		

Note) Theoretical output (N) = Pressure (MPa) x Piston area (mm²)



MGJ

MGP

MGQ

MGG

MGC

MGF

MGZ

MGT

D-□


-X□

Individual
-X□


Series MGQ

Construction/Series MGQM

MGQM12 to 25



50 stroke or less





ø12, ø16



ø20, ø25 Over 50 stroke

MGQM32 to 100



Over 50 stroke

Component Parts

No.	Description	Material	Note
1	Body	Aluminum alloy	Hard anodized
2	Piston	Aluminum alloy	Chromated
3	Piston rod	Stainless steel	ø12 to ø25
		Carbon steel	ø32 to ø100 Hard chrome plated
4	Collar	Aluminum bearing alloy	ø12 to ø40 White anodized
		Aluminum alloy casted	ø50 to ø100 Painted
5	Bushing	Babbitt	ø50 to ø100
6	Head cover	Aluminum alloy	ø12 to ø63 Chromated
			ø80 to ø100 Painted
7	Guide rod	Carbon steel	Hard chrome plated
8	Plate	Carbon steel	Nickel plated
9	Plate mounting bolt	Carbon steel	Nickel plated
10	Guide bolt	Carbon steel	Nickel plated

No.	Description	Material	Note
11	Retaining ring	Carbon tool steel	Phosphate coated
12	Retaining ring	Carbon tool steel	Phosphate coated
13	Bumper A	Urethane	
14	Bumper B	Urethane	
15	Magnet	—	
16	Slide Bearing	Babbitt	
17	Felt	Felt	
18	Holder	Resin	
19	Ball bushing		
20*	Piston seal	NBR	
21*	Rod seal	NBR	
22*	Gasket A	NBR	
23*	Gasket B	NBR	

Replacement Parts: Seal Kit


Bore size (mm)	Kit no.	Description
12	MGQ12-PS	A set of 20, 21, 22 and 23 listed above
16	MGQ16-PS	
20	MGQ20-PS	
25	MGQ25-PS	
32	MGQ32-PS	

* Seal kit includes 20 to 23. Order the seal kit, based on each bore size.

Bore size (mm)	Kit no.	Description
40	MGQ40-PS	A set of 20, 21, 22 and 23 listed above
50	MGQ50-PS	
63	MGQ63-PS	
80	MGQ80-PS	
100	MGQ100-PS	

* Since the seal kit does not include a grease pack, order it separately.
Grease pack part no.: GR-S-010 (10 g)

Bore Size $\phi 32$ to $\phi 100$: MGQM, MGQL



MGQM, MGQL Common Dimensions

Bore size (mm)	Standard stroke (mm)	B	C	DA	F	G	GA	GB	H	J	K	L	MM	ML	NN	P			PW	Q	R	S
																Nil	TN	TF				
32	25, 50, 75, 100, 125, 150, 175, 200	47.5	37.5	16	8	51	12.5	9	114	25	26	38	M8 x 1.25	20	M8 x 1.25	Rc1/8	NPT1/8	G1/8	15	30	96	48
40		54	44	16	8	51	14	10	124	25	26	38	M8 x 1.25	20	M8 x 1.25	Rc1/8	NPT1/8	G1/8	21	30	106	48
50		56	44	20	10	59	14	11	140	29	30	44	M10 x 1.5	25	M10 x 1.5	Rc1/4	NPT1/4	G1/4	27	40	120	56
63		61	49	20	10	72	16.5	13.5	150	35.5	36.5	44	M10 x 1.5	25	M10 x 1.5	Rc1/4	NPT1/4	G1/4	33	50	130	69
80		74.5	56.5	25	16	92	19	15.5	188	45.5	46.5	56	M12 x 1.75	30	M12 x 1.75	Rc3/8	NPT3/8	G3/8	37	60	160	88
100		84	66	30	16	112	23	19	224	55.5	56.5	62	M14 x 2	35	M14 x 2	Rc3/8	NPT3/8	G3/8	40	80	190	108

Bore size (mm)	T	TA	TB	V	W	X	YY	YL	Z
32	112	2	1	80	5	100	M8 x 1.25	11	16
40	122	2	1	90	10	110	M8 x 1.25	11	17
50	138	2	1	100	10	124	M10 x 1.5	12.5	17
63	148	2	1	110	10	132	M10 x 1.5	15	19
80	185	2.5	1.5	140	15	166	M12 x 1.75	18	21
100	221	2.5	1.5	170	15	200	M14 x 2	21	25

MGQM (Slide bearing)/ A, DB, E Dimensions

Bore size (mm)	A	DB	E
32	71.5	20	24
40	71.5	20	17.5
50	81	25	25
63	81	25	20
80	93	28	18.5
100	105	36	21

MGQL (Ball bushing bearing)/ A, DB, E Dimensions

Bore size (mm)	A		DB	E	
	50 st or less	Over 50 st		50 st or less	Over 50 st
32	53	90	16	5.5	42.5
40	54	90	16	0	36
50	60	102	20	4	46
63	61	102	20	0	41
80	84	143	25	9.5	68.5
100	89	153	30	5	69

Note) For intermediate strokes other than standard strokes, refer to the Manufacture of Intermediate Stroke on page 339.


• Rc, NPT and G ports can be selected. (Refer to page 338.)

Grooves (Except $\phi 12$, $\phi 16$, $\phi 20$, $\phi 25$)

Use grooves section "a" and section "b" in the figure below of the cylinder body for firmly fixing in the following case. (Applicable bolt size is M3.)

• These grooves can be used for firmly fixing the tying bands of lead wires of the auto switch, etc., and also terminal boards, etc., to the main body of the cylinder.

• When the terminal block is fixed on a cylinder directly.



Model	A
MGQ□32	8
MGQ□40	8
MGQ□50	8
MGQ□63	8
MGQ□80	10
MGQ□100	10

MGJ

MGP

MGQ

MGG

MGC

MGF

MGZ

MGT

D-□

-X□

Individual
-X□