

# ORDERING DATA

Square body design, insert straight in T-slot, screw 1/4 turn

Output, Function, Cable & Supply Voltage	Order Code	Order Code	Order Code
<b>With flying leads, PUR cable IP67</b>	<b>0,3 metre</b>	<b>3 metre</b>	<b>10 metre</b>
Electronic PNP-NC, with LED, 3-wire, 10-30 V DC	N/A	<b>P8SAGQFAX</b>	<b>P8SAGQFDX</b>
Electronic PNP-NO, with LED, 3-wire, 10-30 V DC	N/A	<b>P8SAGPFAX</b>	<b>P8SAGPFDX</b>
Electronic NPN-NC, with LED, 3-wire, 10-30 V DC	N/A	<b>P8SAGMFAX</b>	<b>P8SAGMFDX</b>
Electronic NPN-NO, with LED, 3-wire, 10-30 V DC	N/A	<b>P8SAGNFAX</b>	<b>P8SAGNFDX</b>
Electric Reed-NO, with LED, 3-wire, 5-30 V AC/DC	N/A	<b>P8SAGSFAX</b>	<b>P8SAGSFDX</b>
Electric Reed-NO, with LED, 2-wire, 5-30 V AC/DC	N/A	<b>P8SAGRFAFAX</b>	N/A
Electric Reed-NO, with LED, 2-wire, 5-230 V AC/DC	N/A	N/A	<b>P8SAGRFDX2</b>
Electric Reed-NC, No LED, 2-wire, 5-120 V AC/DC	N/A	N/A	<b>P8SAGEFRX1</b>
Electric Reed-NC, No LED, 2 wire, 5-30V AC/DC	N/A	N/A	<b>P8SSAGEFRX</b>
<i>Weight: 35 g 3 metre, 105 g 10 metre</i>			
<b>With flying leads, PVC cable IP67</b>	<b>0,3 metre</b>	<b>3 metre</b>	<b>10 metre</b>
Electric Reed-NO, with LED, 3-wire, 5-30 V AC/DC	N/A	<b>P8SAGSFLX</b>	N/A
Electric Reed-NO, with LED, 2-wire, 5-120 V AC/DC	N/A	<b>P8SAGRFLX1</b>	N/A
Electric Reed-NO, with LED, 2-wire, 5-230 V AC/DC	N/A	<b>P8SAGRFLX2</b>	N/A
Electronic PNP-NC, with LED, 3-wire, 10-30 V DC	N/A	<b>P8SAGQFLX</b>	N/A
Electronic PNP-NO, with LED, 3-wire, 10-30 V DC	N/A	<b>P8SAGPFLX</b>	<b>P8SAGPFTX</b>
Electric Reed-NO, with LED, 2-wire, 5-120 V AC/DC	N/A	N/A	<b>P8SAGRFTX1</b>
Electric Reed-NO, with LED, 3-wire, 10-30 V AC/DC	N/A	N/A	<b>P8SAGSFTX</b>
<i>Weight: 35 g 3 metre, 105 g 10 metre</i>			
<b>With M8 knurled screw, PUR cable IP67</b>	<b>0,3 metre</b>	<b>3 metre</b>	<b>10 metre</b>
Electronic PNP-NC, with LED, 3-wire, 10-30 V DC	<b>P8SAGQCHX</b>	N/A	N/A
Electronic PNP-NO, with LED, 3-wire, 10-30 V DC	<b>P8SAGPCHX</b>	N/A	N/A
Electronic NPN-NC, with LED, 3-wire, 10-30 V DC	<b>P8SAGMCHX</b>	N/A	N/A
Electronic NPN-NO, with LED, 3-wire, 10-30 V DC	<b>P8SAGNCHX</b>	N/A	N/A
Electric Reed-NO, with LED, 3-wire, 5-30 V AC/DC	<b>P8SAGSCHX</b>	N/A	N/A
Electric Reed-NC, No LED, 2-wire, 5-30 V AC/DC	<b>P8SAGECNX</b>	N/A	N/A
Electric Reed-NO, with LED, 2-wire, 5-30 V AC/DC	<b>P8SAGRCHX</b>	N/A	N/A
<i>Weight: 15 g 0,3 metre</i>			
<b>ATEX 3G, 3D, IP67</b>	<b>3 metre</b>	<b>5 metre</b>	<b>10 metre</b>
Electronic PNP-NO, with LED, 3-wire, 10-26 V DC, PUR	<b>P8SAGPFAXS</b>	N/A	N/A
<i>Weight: 35 g 3 metre, 55g 5 metre, 105 g 10 metre</i>			
<b>NAMUR 1G, 1D, IP67</b>	<b>3 metre</b>	<b>5 metre</b>	<b>10 metre</b>
NAMUR-NO, with LED, 2-wire, 8,2-20 V DC, PVC	N/A	<b>P8SAGDFMXW *</b>	<b>P8SAGDFTXW *</b>
<i>Weight: 35 g 3 metre, 55g 5 metre, 105 g 10 metre</i>			

**Note:**

-30 to +80 °C (PUR cable) | -30 to + 70 °C (PVC cable) | -25 to +80 °C (NAMUR 1GD | -20 to +50 °C (ATEX 3GD)

All sensors are with an adaptor for S-dovetail Parker type OSP grooves.

\* with an aluminium adaptor