

DOWNLIGHT

Downlight



Features:

Ideal for retrofit of existing CFL fixtures

6 sizes available

Edge-lit LED array with ultra slim profile

Plug and play remote driver

Emergency option available

Die-cast aluminium body

Opal polystyrene diffuser

30,000 hours lifetime [L70/B50]

Construction:

Up to 102 lumens per watt efficacy



DOWNLIGHT

Downlight

Order Codes

All dimensions are in millimetres

Order Code	Description	Lumens(lm)	Total Power(W)	Efficacy(lm/W)	Weight(Kg)
XCDL4WW	4W Downlight - 3000K	300	4	75	0.20
XCDL4NW	4W Downlight - 4000K	350	4	88	0.20
XCDL4DL	4W Downlight - 6000K	350	4	88	0.20
XCDL8WW	8W Downlight - 3000K	600	8	75	0.20
XCDL8NW	8W Downlight - 4000K	650	8	81	0.20
XCDL8DL	8W Downlight - 6000K	650	8	81	0.20
XCDL12WW	12W Downlight - 3000K	1050	12	88	0.31
XCDL12NW	12W Downlight - 4000K	1100	12	92	0.31
XCDL12DL	12W Downlight - 6000K	1100	12	92	0.31
XCDL15WW	13W Downlight - 3000K	1300	13	87	0.40
XCDL15NW	13W Downlight - 4000K	1350	13	90	0.40
XCDL15DL	13W Downlight - 6000K	1350	13	90	0.40
XCDL17WW	17W Downlight - 3000K	1450	17	85	0.55
XCDL17NW	17W Downlight - 4000K	1650	17	97	0.55
XCDL17DL	17W Downlight - 6000K	1650	17	97	0.55
XCDL22WW	22W Downlight - 3000K	2050	22	93	0.81
XCDL22NW	22W Downlight - 4000K	2250	22	102	0.81
XCDL22DL	22W Downlight - 6000K	2250	22	102	0.81

Dimensions

All dimensions are in millimetres

Order Code	Diameter	C	Cut Out
XCDL4WW	90	25	72
XCDL4NW	90	25	72
XCDL4DL	90	25	72
XCDL8WW	120	25	107
XCDL8NW	120	25	107
XCDL8DL	120	25	107
XCDL12WW	170	25	156
XCDL12NW	170	25	156
XCDL12DL	170	25	156
XCDL15WW	200	25	185
XCDL15NW	200	25	185
XCDL15DL	200	25	185
XCDL17WW	238	25	225
XCDL17NW	238	25	225
XCDL17DL	238	25	225
XCDL22WW	296	25	280
XCDL22NW	296	25	280
XCDL22DL	296	25	280

