




Technical datasheet

NJ2217

Single row cylindrical roller bearings

Single row cylindrical roller bearing, single direction for axial loads, separable, pressed steel cage.

Visual(s)



Product definition

d	85 mm
D	150 mm
B	36 mm
E	133.8 mm
F	101.8 mm
d1	108.2 mm
rs min	2 mm
r1s min	2 mm
Radial clearance class	CN
Mass (without HJ ring)	2.58 kg
Brand	NTN

Product performance

Dynamic load, C	170 kN
Static load, C0	218 kN
Fatigue limit load, Cu	25.3 kN
Nlim (oil)	4,800 rpm
Nlim (grease)	4,100 rpm
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.43 Hz
Characteristic rolling element frequency, BSF	7.23 Hz
Characteristic outer ring frequency, BPF0	6.91 Hz
Characteristic inner ring frequency, BPFI	9.09 Hz

Abutment dimensions

da min	94 mm
da max	99 mm
dc min	110 mm
Da max	141 mm
ra max	2 mm

Calculation factors

Equivalent dynamic radial load

$$P = Fr$$

Equivalent static radial load

$$Po = Fr$$