
## Product data sheet





Cordless Impact Wrench

## GDS 18V-1050 HC



Full power at its best: high-torque 3/4" cordless impact wrench with BITURBO Brushless technology and adjustable

#### The most important data

Battery voltage	18 V
Torque, max.	1,050 Nm
No-load speed	0-1,750 rpm

Part Number 0 601 9J8 200

### > More product information

## Technical data

#### Technical data

reciffical data	
Torque adjustment range, min./max., 1st level	0/350 Nm
Torque adjustment range, min./max., 2nd level	0/650 Nm
Torque adjustment range, min./max., 3rd level	0/1050 Nm
No-load speed	0-1,750 rpm
No-load speed (1st level)	0-800 rpm
No-load speed (2nd level)	0-1,300 rpm
No-load speed (3rd level)	0-1,750 rpm
Torque settings	3
Weight excl. battery	2.9 kg
Torque, max.	1,050 Nm
Impact rate	0-2,600 bpm
Impact rate (1st level)	0-1,600 bpm
Impact rate (2nd level)	0-2,300 bpm
Impact rate (3rd level)	0-2,600 bpm
Battery voltage	18 V
Tool holder	3/4" Square
Breakaway torque, max.	1,700 Nm

<sup>&#</sup>x27;Total vibration values (Tightening screws and nuts of maximum permitted size)'

Vibration emission value ah	13.5 m/s <sup>2</sup>
Uncertainty K	1.5 m/s <sup>2</sup>
Screw diameter	
Screw diameter	M 14 - M 24

## Noise/vibration information

#### Tightening screws and nuts of maximum permitted size

Vibration emission value ah	13.5 m/s <sup>2</sup>
Uncertainty K	1.5 m/s <sup>2</sup>

# Invented for life

## Product data sheet

#### Power tools for trade & industry

# Advantages:

- BITURBO Brushless technology for powerful tightening and breakaway torque of 1,050 Nm and 1,700 Nm
- User interface with two default modes, metal (A) and wood (B). Further modes can be adjusted and individualised via the Toolbox App
- Three speed/torque settings for high versatility and controlled power

















