



Technical datasheet

NU2224

Single row cylindrical roller bearings

Single row cylindrical roller bearing, floating, separable, pressed steel cage

Visual(s)



Product definition

d	120 mm
D	215 mm
B	58 mm
E	191.5 mm
F	143.5 mm
rs min	2.1 mm
r1s min	2.1 mm
Radial clearance class	CN
Mass (without HJ ring)	8.19 kg
Brand	NTN

Product performance

Dynamic load, C	350 kN
Static load, C0	460 kN
Fatigue limit load, Cu	48.1 kN
Nlim (oil)	3,400 rpm
Nlim (grease)	2,900 rpm
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.43 Hz
Characteristic rolling element frequency, BSF	6.84 Hz
Characteristic outer ring frequency, BPF0	6.42 Hz
Characteristic inner ring frequency, BPF1	8.58 Hz

Abutment dimensions

da min	131 mm
da max	141 mm
db min	146 mm
Da max	204 mm
ra max	2 mm
r1a max	2 mm

Calculation factors

Equivalent dynamic radial load

$$P = F_r$$

Equivalent static radial load

$$P_0 = F_r$$