Bench drilling machine - HU 20-2 Topline ...

Description

Table drilling machine of superior quality. Equipped with heavy duty back plate which prevents vibration. The spring pressure and the engraved nonius can easily be set. Protective drill chuck cover made of high quality polycarbonate, that complies with the latest safety standards. The machine stops when the drill chuck cover is opened. Separate emergency switch that can easily be reached. Autostop switch is activated when the v-belt cover is opened. V-belt pulley runs over dovetail guide for a minimum of vibrations.

- quick-release drill head 1-16 mm (B16)
- depth stop
- low-noise engine
- table height adjustable
- production machine
- telescopic protective cover

Documents

🔀 manual-11222-en 🔗

manual-11224-en 🔗

Accessory optional

Drill clamp with prism jaw BKL K-100-QP 20112300

Set HSSE Twisted drills, ground, 19 pcs

Protection cover HBSK 180 Set 40420

HB499 1-13 / 0.5 12991019

Drill chuck arbor with MT shank MTB 2 ADAPT B16 20112263

Keyless drill chuck DC 1016-B16-ECO 20112240

Drill clamp with prism jaw BKL K-100-P 20112215

Drill clamp with prism jaw BKL K-150-P 20112218













	HU 20-2 Topline	HU 20-4 Topline
	Item no. 11222	Item no. 11224
Speed range	140 - 2300 rpm	230 - 2350 rpm
Number of revs	12	24
Net weight	75 kg	85 kg
Pole changing motor	No	yes
Voltage	230 V	400 V
Brand	Huvema Machine tools	Huvema Machine tools

General specifications

- Drilling capacity: 22 mm
- Orilling depth: 80 mm
- Spindle taper: MT2
- Oistance spindle-column: 185 mm
- Oclumn diameter: 78 mm
- Foot dimensions: 450 x 300 mm
- Packing dim.: 850 x 570 x 320 mm
- ▼ Engine power: 1,1 kW



Website HU 20-2 Topline 🔗

