


The Timken Company

4500 Mt Pleasant St. NW


N. Canton, OH 44720

Phone: (234) 262-3000

E-Mail: CustomerCAD@timken.com • **Web site:** www.timken.com

Part Number 468, Tapered Roller Bearings - Single Cones - Imperial

This is the most basic and most widely used type of tapered roller bearing. It consists of two main separable parts: the cone (inner ring) assembly and the cup (outer ring). It is typically mounted in opposing pairs on a shaft.



[Specifications](#) | [Dimensions](#) | [Abutment and Fillet Dimensions](#) | [Basic Load Ratings](#) | [Factors](#)

Specifications

Series	455
Cone Part Number	468
Design Units	Imperial
Cage Type	Stamped Steel
C1 - Dynamic Radial Rating (Two-Row, 1 million revolutions)¹	62900 lbf 280000 N
C90(2) - Dynamic Radial Rating (Two-Row, 90 million revolutions)²	16300 lbf 72600 N



Dimensions

d - Cone Bore	2 1/16 in 52.388 mm
----------------------	------------------------

B - Cone Width	1.1542 in 29.317 mm
-----------------------	------------------------

Abutment and Fillet Dimensions

R - Cone Backface "To Clear" Radius³	0.060 in 1.5 mm
--	--------------------

da - Cone Frontface Backing Diameter	2.36 in 60 mm
---	------------------

db - Cone Backface Backing Diameter	2.44 in 62 mm
--	------------------

Ab - Cage-Cone Frontface Clearance	0.08 in 2 mm
---	-----------------

Aa - Cage-Cone Backface Clearance	0.07 in 1.8 mm
--	-------------------

a - Effective Center Location⁴	-0.28 in -7.1 mm
--	---------------------

Basic Load Ratings

C90 - Dynamic Radial Rating (90 million revolutions)⁵	9370 lbf 41700 N
---	---------------------

C1 - Dynamic Radial Rating (1 million revolutions)⁶	36100 lbf 161000 N
---	-----------------------

C0 - Static Radial Rating	37200 lbf 166000 N
----------------------------------	-----------------------

C_{a90} - Dynamic Thrust Rating (90 million revolutions)⁷	5380 lbf 23900 N
---	---------------------

Factors

K - Factor⁸	1.74
G1 - Heat Generation Factor (Roller-Raceway)	58.6
G2 - Heat Generation Factor (Rib-Roller End)	17.1
Cg - Geometry Factor⁹	0.0946

¹ Based on 1×10^6 revolutions L_{10} life, for the ISO life calculation method.

² Based on 90×10^6 revolutions L_{10} life, for The Timken Company life calculation method. C_{90} and C_{a90} are radial and thrust values for a single-row, $C_{90(2)}$ is the two-row radial value.

³ These maximum fillet radii will be cleared by the bearing corners.

⁴ Negative value indicates effective center inside cone backface.


⁵ Based on 90×10^6 revolutions L_{10} life, for The Timken Company life calculation method. C_{90} and C_{a90} are radial and thrust values.

⁶ Based on 1×10^6 revolutions L_{10} life, for the ISO life calculation method.

⁷ Based on 90×10^6 revolutions L_{10} life, for The Timken Company life calculation method. C_{90} and C_{a90} are radial and thrust values for a single-row, $C_{90(2)}$ is the two-row radial value.

⁸ These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.

⁹ Geometry constant for Lubrication Life Adjustment Factor a_3 .



IMPERIAL UNITS

Number of Rollers Per Row <
--