



## Accessory Devices - Silencers

Silencers, NPT Threads      Metal Construction



### Canister-Style Silencer - NPT Threads



Recommended for pressures up to 125 PSI. Construction of brass and zinc-plated steel.

| Part Number | A                | B<br>(in.) | C<br>(in.) | Flow (SCFM)<br>At 90 psi | Weight<br>(oz.) |
|-------------|------------------|------------|------------|--------------------------|-----------------|
| R432012062  | 1/8-27 NPT       | 1.38       | 0.43       | 44                       | 0.02            |
| R432012060  | 1/4-18 NPT       | 1.75       | 0.56       | 96                       | 0.05            |
| R432012058  | 3/8-18 NPT       | 2.10       | 0.68       | 200                      | 0.08            |
| R432011952  | 1/2-14 NPT       | 2.75       | 0.87       | 450                      | 0.50            |
| R432012059  | 3/4-14 NPT       | 3.15       | 1.06       | 560                      | 0.30            |
| R432012057  | 1-11 1/2 NPT     | 3.87       | 1.31       | 800                      | 0.50            |
| R432012061  | 1 1/4-11 1/2 NPT | 4.50       | 1.68       | 1120                     | 0.85            |


### Sintered Bronze Cone Silencer - NPT Threads



Recommended for pressures up to 125 PSI. Construction of brass and bronze. Porosity: 40 micron

| Part Number | A          | B<br>(in.) | C<br>(in.) | D<br>(in.) |
|-------------|------------|------------|------------|------------|
| R432000825  | 1/8-27 NPT | 7/16       | 0.89       | 0.50       |
| R432000826  | 1/4-18 NPT | 9/16       | 1.28       | 0.65       |
| R432000827  | 3/8-18 NPT | 11/16      | 1.52       | 0.81       |
| R432000828  | 1/2-14 NPT | 7/8        | 1.98       | 1.03       |
| R432000829  | 3/4-14 NPT | 1 1/16     | 2.28       | 1.25       |

### Sintered Bronze Breather/Vent - NPT Threads



Recommended for pressures up to 125 PSI. Construction of brass and bronze. Porosity: 90 micron

| Part Number | A          | B<br>(in.) | C<br>(in.) | D<br>(in.) |
|-------------|------------|------------|------------|------------|
| R432000830  | 1/8-27 NPT | 0.40       | 7/16       | 0.50       |
| R432000831  | 1/4-18 NPT | 0.68       | 9/16       | 0.65       |
| R432000832  | 3/8-18 NPT | 0.79       | 11/16      | 0.81       |
| R432000833  | 1/2-14 NPT | 0.97       | 7/8        | 1.03       |
| R432000834  | 3/4-14 NPT | 1.06       | 1 1/16     | 1.25       |