

Insertion Black Rubber

Features embedded textile reinforcement for added increased tensile strength and tear resistance

- Suitable for use in air, hot water and hydraulic services.
- A popular gasket material for applications with high compression loads.
- 68 degrees shore A hardness.
- Tensile strength at break: 3.0 Mpa.
- Elongation at break: 200%.



Parts

Part Number	Size	Colour	Weight
IRS00001	1.4 m x 10 m x 1.8 mm	Black	47.00 kg
IRS00002	1.4 m x 10 m x 3 mm	Black	71.15 kg
IRS00003	1.4 m x 10 m x 4.5 mm	Black	94.50 kg
IRS00004	1.4 m x 10 m x 6 mm	Black	130.50 kg
IRS00005	1.4 m x 5 m x 10 mm	Black	110.50 kg
IRS00006	1.4 m x 5 m x 12 mm	Black	131.30 kg

Technical Specification

Material	SBR
Surface Finish	Smooth
Product Height	1.8 mm-25 mm
Roll Length	5 m or 10 m
Operating Temperature	-30°C to +80°C
Other Product Performance Information	Test Temperature: 25°C Relative Humidity: 35% Correlation criterion: GB/T528-1998 GB/T3512-1989 GB/T531-1992
Country of Origin	China