

5-DIE UNIVERSAL CRIMPING PLIERS

Description

5 different types of lugs to cover all your crimping applications. Rapid change of a die in 5 seconds. Automatic Die Engagement System. Ease of use thanks to a carefully designed centre of gravity, angled head and ergonomic handles. Automatic declutching of the clamp for better crimping. Constant crimping quality thanks to the precision profiles and the blocking. Chromium-vanadium steel, oil-soaked and tempered. Crimping pressure set and calibrated at the factory, adjustable. Brilliant head and bi-material handles. Storage (5 dices) with fastening clip belt. Contents: Non-insulated splice connectors: 0. 5-1. 5/1. 5-2. 5/4. 0-6. 0/et + 6. 0-10. 0 mm² (20-8 AWG) Uninsulated lugs with open barrels: 0. 5-6,0 mm² (20-10 AWG) Preinsulated lugs: 0. 5-6. 0 mm² (20-10 AWG) Cable tips: 0. 25 to 6. 0 mm² (24-10 AWG) Cable tips: 10/ 16/ 25 mm² (8-4 AWG) German made.



Strong points

Strength ratio improved of 35% better than regular crimping pliers

Characteristics

Ref.	EAN	Lead terminal diameter mm ²	Number of elements
845359	3660338076145	0.5/6	5