# **Color Ratchet & Color Speeder**

#### **Color ratchet**



## **Color Speeder for Ratchet Thimble Micrometer**



04GAA899 Black

04GAA900 Red 04GAA901 Yellow 04GAA902 Green 04GAA903 Blue 04AAB208 Gray

Red

Blue

Yellow

Green

Brown

Gray

Gray

Gray

985061

985081

985071

985076

985066

04GZA241\* 04GZA239\*\*

04GZA243\*\*\*

#### **Technical Data**

Tip length: metric type:  $10 \text{mm} \pm 5 \mu \text{m}$  inch type:  $.5" \pm .0002"$ 

inch type. .5 ±.00

Spindle Dia: \*1 .250" / 6.35mm

\*1 Spindle diameter for 101469 (.250" ball) is .315"/8mm



To measure odd workpieces, several convenient anvil attachments are prepared by Mitutoyo. Among them the most often used one is the ball attachment.

The ball attachments are hardened steel balls with .200" and .250" diameters which are placed on the .250" and .315" diameter anvils, respectively, by rubber caps. With these attachments, regular micrometers can measure cylindrical wall thickness, but, .200" or .250" must be subtracted from the readings.

Other attachments shown here are either .500" or 10mm in length. The added amount must be subtracted from the reading.

# Spindle Attachment Tip

Rall



101468 (.200" ball dia.) 101469 (.250" ball dia.)



Spline

a.) 208062 a.) 208098



208062\* 208063\* 208098 208099

Comparator



208064\* 208100



208065\* 208101



208066\* 208102

#### **DIMENSIONS**

Order No.	Dimension
208098 208062*	
208099 208063*	30°
208100 208064*	- O O O O O O O O O O O O O O O O O O O

Order No.	Dimension
208101 208065*	30°
208102 208066*	ø12.7

<sup>\*</sup> metric type

### **Micrometer Oil**

**207000** (30ml)





<sup>\*</sup>for Series 293 digital model

<sup>\*\*</sup> up to 300mm / 12" \*\* over 300mm / 12"