

L-ALB, B-ALB, BH-ALB series

**Pressed steel castors, medium-duty version,
with top plate, wheel with
Blickle Besthane® polyurethane tread**

 250–500 kg

Bracket: L/B/BH series

- pressed steel, zinc-plated, blue-passivated, Cr6-free

Swivel bracket:

- double ball bearing in the swivel head
- strong central kingpin (from wheel Ø 150 mm)
- swivel head seal
- minimum swivel head play and smooth rolling characteristic and increased service life due to the special dynamic Blickle riveting process

Wheel: ALB series

- tread: high-quality polyurethane elastomer Blickle Besthane®, hardness 92 Shore A, colour brown, non-marking, non-staining
- wheel centre: die-cast aluminium, colour silver grey


Additional details:

- bracket series: page 91
- brakes: page 112–113
- wheel series: page 307
- bearing types: page 84–85



 **Blickle
Besthane®**

5



Swivel castors	Fixed castors	Swivel castors with “stop-fix” brake	Wheel Ø [mm]	Wheel width [mm]	Load capacity [kg]	Bearing type	Total height [mm]	Plate size [mm]	Bolt hole spacing [mm]	Bolt hole Ø [mm]	Offset swivel castor [mm]
L-ALB 101K	B-ALB 101K	L-ALB 101K-FI	100	40	250	ball bearing	125	100 x 85	80 x 60	9	35
L-ALB 125K	B-ALB 125K	L-ALB 125K-FI	125	40	250	ball bearing	150	100 x 85	80 x 60	9	38
L-ALB 150K	B-ALB 150K	L-ALB 150K-FI	150	50	400	ball bearing	190	140 x 110	105 x 75–80	11	60
L-ALB 160K	B-ALB 160K	L-ALB 160K-FI	160	50	400	ball bearing	195	140 x 110	105 x 75–80	11	60
L-ALB 200K	B-ALB 200K	L-ALB 200K-FI	200	50	400	ball bearing	235	140 x 110	105 x 75–80	11	65
L-ALB 250K-3	BH-ALB 250K	*	250	60	500	ball bearing	295	140 x 110	105 x 75–80	11	77

* “stop-top” brake version, see versions / options

Versions / options



	with “stop-top” brake	with “central-stop” central brake system	directional lock (sepa- rate) 1 x 360°	directional lock (sepa- rate) 1 x 360°	with steel foot guard
Technical description page	112	113	115	115	116
Product code suffix	-ST	-CS11	RI-03.01	RI-05.03	-FS
Available for	all	wheel Ø 160–200 mm	wheel Ø 100–125 mm**	wheel Ø 150–200 mm**	all

** Only for swivel castors without brake or swivel castor with “stop-top” and “central-stop” brake upon request