

# Duo spiral plastic tubing PUN-6X1-S-2-DUO-BS

Part number: 197621

FESTO



 General operating condition

## Data sheet

| Feature                                  | Value                                                                                                          |
|------------------------------------------|----------------------------------------------------------------------------------------------------------------|
| Working length                           | 2 m                                                                                                            |
| Outside diameter                         | 6 mm                                                                                                           |
| Block length                             | 0.836 m                                                                                                        |
| Inside diameter                          | 4 mm                                                                                                           |
| Winding diameter                         | 46 mm                                                                                                          |
| Number of turns                          | 52                                                                                                             |
| Temperature-dependent operating pressure | -0.95 bar ... 10 bar                                                                                           |
| Approval                                 | German Technical Control Board (TÜV)                                                                           |
| Certificate issuing authority            | B 013277 0506 00                                                                                               |
| Operating medium                         | Compressed air to ISO 8573-1:2010 [7:-:-]                                                                      |
| LABS (PWIS) conformity                   | VDMA24364-B2-L                                                                                                 |
| Ambient temperature                      | -35 °C ... 60 °C                                                                                               |
| Product weight                           | 230 g                                                                                                          |
| Pneumatic connection                     | For push-in connector O.D. 6 mm<br>For barbed fitting I.D. 4 mm with union nut<br>For barbed fitting I.D. 4 mm |
| Colour                                   | Blue/black                                                                                                     |
| Shore hardness                           | D 52 +/- 3                                                                                                     |
| Material tubing                          | TPE-U(PU)                                                                                                      |