

Pilot valve

- CNOMO / NFE 49-003-1

- 581, Modular system



Standards

Working pressure min./max.

Ambient temperature min./max.

Medium

Protection class with connection

Duty cycle

Weight

CNOMO / NFE 49-003-1

See table below

-10 ... 50 °C

Compressed air

IP65

100 %

See table below

An example configuration is illustrated.
The delivered product may thus deviate
from the illustration.

Technical data

Part No.		MO	Operational voltage DC	Operational voltage AC 50 Hz
5428110080			-	230 V
5420890020			24 V	-
5420850020			24 V	-
5428150080			-	230 V
5420890030			48 V	-
5420890070			110 V	-
5420890080			220 V	-
5428110020			-	24 V
5428110040			-	48 V
5428110070			-	110 V

Part No.	Voltage tolerance DC	Voltage tolerance AC 50 Hz	Power consumption DC	Holding power AC 50 Hz
5428110080	-	-20% / +10%	-	8 VA
5420890020	-10% / +10%	-	2 W	-
5420850020	-10% / +10%	-	6,7 W	-
5428150080	-	-20% / +10%	-	8 VA
5420890030	-10% / +10%	-	2 W	-
5420890070	-10% / +10%	-	2 W	-
5420890080	-10% / +10%	-	2 W	-
5428110020	-	-20% / +10%	-	8 VA
5428110040	-	-20% / +10%	-	8 VA
5428110070	-	-20% / +10%	-	8 VA

Part No.	Switch-on power AC 50 Hz	Working pressure min./max.	Power consumption
5428110080	10 VA	0 ... 10 bar	-